



HOT WATER PRESSURE WASHER

GAS DRIVEN / DIESEL FIRED



Adjustable thermostat
up to 93°C/200°F with illuminated rocker switch and hour meter

American made
heavy duty 7,000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with center balanced lift hook (above industry standards)

Lifting hook

Power electric start with 18amp charge

HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe

Triplex direct-drive **Centurion** pump

96' length coil for maximum heat rise and proper heat production, 5,500 PSI rated

12" oil drain hose for ease of maintenance

Stainless-steel coil skin provides extra durability and resists corrosion

Brake assembly

12v DC Oil-fired Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

28 L/7.4 gal removable, rust-proof polyethylene fuel tank with fuel gauge in cap

Marine sealed battery box with 55 AH AGM deep cycle battery

TMR / TRUCK MOUNT READY
mounting bracket

13" heavy-duty flat free tires

3/4" HD Threaded mount axle

FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose with quick connects
- Adjustable low pressure chemical injector assembly with quick connects
- 3 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



360° Hose reel swivel bracket
(sold separately: 59,400.001)

DIRECT DRIVE

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4415PA	4.2	4,400	420	POWEREASE 420	330,000	CENTURION PUMP CTG2	DIRECT	2.21 GPH	48"L x 32"W x 46"H	45"L x 33"W x 52"H	580



HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

ACCESSORY OPTIONS

500195	HOSE REEL - 360° PIVOT, 150' MAX LENGTH, 300° F (STEAM RATED SWIVEL) COMES WITH WHIP HOSE
59.400.001	360° HOSE REEL SWIVEL BRACKET
85.205.090	SPRAY GUN WITH DUAL WAND TO SWITCH FROM PRESSURE TO SOAPER BARREL
85.490.016	SOOT REMOVER, 125 ML (4 OZ)
85.403.009	20" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 180° F
85.210.140	TURBO ROTARY NOZZLE, 4.0 ORIFICE, 5,000 PSI
85.490.015	FUEL STABILIZER, 236.6 ML (8 OZ)
59.400.004	7" RAIN CAP / EXHAUST CHIMNEY

HOSE REEL FEATURES

- **Hose Capacity:** 150' x 3/8"
- **Hose Axle:** Stops hose from kinking when attached to hose reel axle. Eliminates wear on hose, for longer life
- **Adjustable Friction Brake:** Eliminates hose backlash when unwinding
- **Heavy-Duty Performance:** Super Swivel rated to 5,000 PSI & 325°F standard
- **Easy Push/Pull Spring Loaded Lock Pin:** Prevents unwanted hose unwinding
- **Multi-Position Collar with Spring Loaded Lock Pin:** Allows reel to be positioned in a variety of positions and locked
- **Durable Construction:** Heavy gauge cold rolled metal. Durable reel, capable of securely storing high pressure hose.
- **Easy Turn Handle:** Prevents fatigue when coiling your hose
- **Hose Guide:** Allows for easy hose rolling & prevents tangling
- **Double Bearing Design with Stainless Steel Shaft:** Prevents side movement and allows reel to swivel freely
- **Locking Collar Shaft:** Prevents reel from sliding out of the bracket vertically
- **Smooth Radius Bent Arm:** Eliminates 90° bend and strengthens the arm



500195

SWIVEL REEL



59.400.001



59.400.004



85.210.140



85.205.090



85.490.016



85.490.015



85.403.010



85.403.032



85.403.009