Bedrosians[®] Tile & Stone



Frost 100001576 - 12"x72" Rectified Field Tile - Honed



Acorn 100001574 - 12"x72" Rectified Field Tile - Honed



Nest 100001577 - 12"x72" Rectified Field Tile - Honed





Bark 100001575 - 12"x72" Rectified Field Tile - Honed

Meadow 100002269 - 12"x72" Rectified Field Tile - Honed






SIZING & PACKAGING

Туре	Shape	Acorn Code	Bark Code	Frost Code	Nest Code	Meadow Code	Size	Description	Pcs/Ctn	Sf/Ctn
Field		100001574	100001575	100001576	100001577	100002269	12"x72"	Rectified Field Tile - Honed	4	23.35

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	N/A	Unaffected	7	≥350 lbf	≤0.5%	Unaffected

Shade Variation



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	٠	۲	۲	٠	۲	۲
Commercial	٠	۲		•	۲	۲



LEGEND

	J			or Interior use only Special Order only	† May be suital	ble for Exterior Floors	
Made in USA	Glazed-Color Body Porcelain	Rectified Edge	Recycled Content	P RCELAIN		GREENGUARD	



Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improver installation, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.



bedrosians.com