


White Carrara/White Thassos 100001720 Mosaic Blend - Honed (15 3/4"x15 3/4" Sheet)



White Carrara/Bardiglio 100001721 Mosaic Blend - Honed (15 3/4"x15 3/4" Sheet)



Myra Beige/Basalt 100001723 Mosaic Blend - Honed (15 3/4"x15 3/4" Sheet)



Nero Marquina/Bardiglio/Myra Beige 100001722 Mosaic Blend - Honed (15 3/4"x15 3/4" Sheet)



SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs/Ctn	Sf/Ctn
Mosaic	O O O O O O O O O O	100001723	153/4"x153/4"Sheet	Mosaic Blend - Honed in Myra Beige/Basalt	5	8.60
	00000000 00000000000000000000000000000	100001722	153/4"x153/4"Sheet	Mosaic Blend - Honed in Nero Marquina/Bardiglio/Myra Beige	5	8.60
	0000000 000000000000000000000000000000	100001721	153/4"x153/4"Sheet	Mosaic Blend - Honed in White Carrara/Bardiglio	5	8.60
		100001720	153/4"x153/4"Sheet	Mosaic Blend - Honed in White Carrara/White Thassos	5	8.60

ANSITECHNICAL SPECIFICATIONS

	Abrasion Resistance	Water Absorption	Average Bulk Specific Gravity	Compressive Strength Perpendicular (Dry)	Flexural Strength Perpendicular (Dry)	Modulus Rupture Perpendicular (Dry)
Results	11.98 lw	0.16	167.28 lbs/ft³ 2,680.6 kg/m³	13,000 psi	1,340 psi	1,500 psi

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	• †	•	•	•†	•	
Commercial	• †	•	•	•†	•	

LEGEND

 Product rated for Interior & Exterior use Product rated for Interior use only † May be suitable for Exterior Floors

Please be aware that white stones installed on shower floors may experience oxidization and rusting

All natural stone products must be sealed prior to grouting.

 \varnothing Applications & ANSI Technical Specifications do not apply

 $Do \ not \ use \ chlorine, a cids, or \ other \ harsh \ chemicals \ to \ clean. \ All \ spills \ must \ be \ cleaned \ immediately \ to \ prevent \ staining.$

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Natural stone has inherent variation in color/shade, size, texture, finish, veining, grain, movement and pitting. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Ensure proper installation, application, use, care and maintenance. Natural stone must be sealed prior to installation. Do not use aerosol catalyst adhesives. Only use pH neutral cleaners. Natural stone may experience changes in color and finish if installation an exterior application. There is no warranty for natural stone. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

Shade Variation

