

Field Tile Sizes



Blanc - BLA
CRDBARBLA840 - 8"x40" Rectified Field Tile - Matte



Ecrú - ECR
CRDBARECR840 - 8"x40" Rectified Field Tile - Matte



Gris - GRS
CRDBARGRS840 - 8"x40" Rectified Field Tile - Matte



Bleu - BLE
CRDBARBLE840 - 8"x40" Rectified Field Tile - Matte



Brun - BRU
CRDBARBRU840 - 8"x40" Rectified Field Tile - Matte



Vert - VER
CRDBARVER840 - 8"x40" Rectified Field Tile - Matte



Fonce - FON
CRDBARFON840 - 8"x40" Rectified Field Tile - Matte



Noir - NOI
CRDBARNOI840 - 8"x40" Rectified Field Tile - Matte



Barrique

Glazed Color Body Porcelain

Photo Features 4"x40" and 8"x40" Rectified Field Tile - Matte in Brun.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		CRDBAR***840	8"x40"	Rectified Field Tile - Matte	5	10.76

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	Pass ≤ 175 (ISO)	Unaffected	N/A	Pass (1,300 ISO)	≤ 0.5%	Unaffected


Shade Variation



V3-Moderate


APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	■	■	● †	■	■
Commercial	● †	■	■	● †	■	■



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ⊘ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

