



Early Grey - EAG
DECAVOEAG28 - Brick



Sidewalk - SID
DECAVOSID28 - Standard Brick



Used Red - USR
DECAVOUSR28 - Antik Brick



Photo Features 2"x8" Brick - Matte in Early Grey.



Avondale

Decorative (Brick)

Photo Features 2"x8" Brick - Matte in Early Grey.


SIZING & PACKAGING

| Type | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|-------|-------|-------------|-------|---|-----------|----------|
| Field | | DECAVOUSR28 | 2"x8" | Antik Brick - Matte (Used Red Brick) | 72 | 11.08 |
| | | DECAVOEAG28 | 2"x8" | Brick - Matte (Early Gray - Signature Color) | 70 | 9.43 |
| | | DECAVOSID28 | 2"x8" | Standard Brick - Matte (Sidewalk - Premium Color) | 70 | 9.43 |

ANSI TECHNICAL SPECIFICATIONS

| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|-----------------|------------------------------|-----------------------------------|-------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Results | ≥ 0.42 | N/A | Unaffected | 7 | ≥ 250 lbf | > 1.0 (Ceramic) | Unaffected |

Shade Variation



APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|-------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | ● † | ◻ | ◻ | | ◻ | |
| Commercial | ● † | ◻ | ◻ | | ◻ | |

LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ◻ Applications & ANSI Technical Specifications do not apply
- * Special Order only

This product may be installed near or on the face of high-heat areas, but not inside. This product cannot be installed in showers, pools, spas, or waterline applications. Do not use chlorine, acids, or other harsh chemicals to clean. Use only sanded grout with this product. This handmade product may vary in sizing. Use a minimum 1/2" grout joint. Brick tiles must be sealed before and after grouting to prevent penetration. Seal grout joints as well. For a low sheen, Master Seal 100 by Desert Brand is the recommended topical sealer. For a matte finish, use a high quality penetrating sealer. All spills must be cleaned immediately to prevent staining. These tiles are handmade and subject to color variation. Mix randomly from different boxes to balance variation. Wet the back of the tile prior to setting. Apply mortar to both the substrate and the back of the brick tile using a 1/2" notched trowel.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

