



2 1/2"x9" Field Tile - Gloss or Matte



Ø Milky Way (MIW) - Gloss
DECZENMIW259G



Moon (MOO) - Matte
DECZENMOO259M



Solar (SOL) - Matte
DECZENSOL259M




Orion (ORI) - Matte
DECZENORI259M



Ø Tide (TID) - Gloss
DECZENTID259G



Umbra (UMB) - Matte
DECZENUMB259M



Ø Orbit (ORB) - Matte
DECZENORB259M



Gravity (GRA) - Matte
DECZENGRA259M

2"x6" Mosaic - Gloss or Matte (11 1/2"x 11 1/4" Sheet)



Ø Milky Way (MIW) - Gloss
DECZENMIW26GMO



Moon (MOO) - Matte
DECZENMOO26MMO



Solar (SOL) - Matte
DECZENSOL26MMO




Orion (ORI) - Matte
DECZENORI26MMO



Ø Tide (TID) - Gloss
DECZENTID26GMO



Umbra (UMB) - Matte
DECZENUMB26MMO



Ø Orbit (ORB) - Matte
DECZENORB26MMO



Gravity (GRA) - Matte
DECZENGRA26MMO



Photo Features 2 1/2"x9" Field Tile - Matte in Moon.

Zenia

Decorative (Glazed Porcelain)

Photo Features 2 1/2"x9" Field Tile - Matte in Moon.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field Tile		∅ DECZEN***259G	2 1/2"x9"	Field Tile - Gloss	64	9.60
		DECZEN***259M	2 1/2"x9"	Field Tile - Matte	64	9.60
Mosaic		∅ DECZEN***26GMO	11 1/2"x11 1/4" Sheet	2"x6" Mosaic - Gloss	10	8.90
		DECZEN***26MMO	11 1/2"x11 1/4" Sheet	2"x6" Mosaic - Matte	10	8.90

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650	Bond Strength A137.2-7.7	Thermal Shock ASTM# C484
Results	≥ 0.42	7	≥ 350 lbf	≤ 0.5%	Unaffected	Pass	N/A

Shade Variation



V2-Slight

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	● (Matte Only)	◻	◻
Commercial	● (Matte Only)	◻		● (Matte Only)	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Do not use acidic cleaners on the Orbit color in this collection. Use of acidic products voids warranty.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

