

Field Tile Sizes



Light - LIG
FLOURBLIG1632 - 16"x32" Rectified - Matte
FLOURBLIG3232 - 32"x32" Rectified - Matte



Plomb - PLO
FLOURBPLO1632 - 16"x32" Rectified - Matte
FLOURBPLO3232 - 32"x32" Rectified - Matte



Charbon - CHA
FLOURBCHA1632 - 16"x32" Rectified - Matte
FLOURBCHA3232 - 32"x32" Rectified - Matte



Russet - RUS
FLOURBRUS1632 - 16"x32" Rectified - Matte
FLOURBRUS3232 - 32"x32" Rectified - Matte

Paver Sizes



Light - LIG
FLOURBLIG882CM
8"x8" 2cm Paver - Matte



Plomb - PLO
FLOURBPLO882CM
8"x8" 2cm Paver - Matte



Charbon - CHA
FLOURBCHA882CM
8"x8" 2cm Paver - Matte



Russet - RUS
FLOURBRUS882CM
8"x8" 2cm Paver - Matte



Light - LIG
FLOURBLIG8122CM
8"x12" 2cm Paver - Matte



Plomb - PLO
FLOURBPLO8122CM
8"x12" 2cm Paver - Matte



Charbon - CHA
FLOURBCHA8122CM
8"x12" 2cm Paver - Matte



Russet - RUS
FLOURBRUS8122CM
8"x12" 2cm Paver - Matte



Urban Style

Glazed Color Body Porcelain & Pavers

Photo Features 32"x32" Rectified Field Tile - Matte in Charbon.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		FLOURB***1632	16"x32"	Rectified Field Tile - Matte	3	10.33
		FLOURB***3232	32"x32"	Rectified Field Tile - Matte	2	13.78
Pavers		FLOURB***882CM	8"x8"	2CM Pavers - Matte	12	5.27
		FLOURB***8122CM	8"x12"	2CM Pavers - Matte	7	4.63

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	Pass ≤ 175 (ISO)	Unaffected	N/A	Pass (1,300 ISO)	≤ 0.5%	Unaffected

Shade Variation




APPLICATIONS - TILE

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●†	◻	◻	●†	◻	◻
Commercial	●†	◻	◻	●†	◻	◻


APPLICATIONS - 2CM

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	◻	◻	◻	◻	◻	◻
Commercial	◻	◻	◻	◻	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

