

Field Tile Sizes



Calacatta - C
TCRCAL36CP - 12"x24" Polished



Calacatta - C
TCRCAL60CP - 24"x24" Polished

Available Mosaics



Calacatta - C
TCRCAL12HERCP
1"x2" Herringbone Mosaic - Polished
(11 3/4"x12 1/2" Sheet)



Calacatta - C
TCRCAL221HEXCP
2"x2" Hexagon Mosaic - Polished
(12 1/2"x12 1/2" Sheet)

Calacatta

Glazed Porcelain

Photo Features 24"x24" Field Tile - Matte in Calacatta.


SIZING & PACKAGING

| Type | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|--------|-------|----------------|-----------------------|-------------------------------------|-----------|----------|
| Field | | TCRCAL36CP | 12"x24" | Field Tile - Polished | 9 | 18.00 |
| | | TCRCAL60CP | 24"x24" | Field Tile - Polished | 4 | 16.00 |
| Trim | | TCRCALS324CP | 3"x24" | Surface Bullnose - Polished | 26 | - |
| Mosaic | | TCRCAL12HERCP | 11 3/4"x12 1/2" Sheet | 1"x2" Herringbone Mosaic - Polished | 11 | - |
| | | TCRCAL221HEXCP | 12 1/2"x12 1/2" Sheet | 2"x2" Hexagon Mosaic - Polished | 12 | - |

ANSI TECHNICAL SPECIFICATIONS

| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|-----------------|------------------------------|-----------------------------------|-------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Results | N/A | 4 | Unaffected | 6 | ≥ 250 lbf | ≤ 0.5% | Unaffected |


Shade Variation



V3-Moderate


APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|------------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | • | ◻ | • | | ◻ | |
| Light Commercial | | ◻ | | | ◻ | |
| Commercial | | ◻ | | | ◻ | |



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ⊘ Applications & ANSI Technical Specifications do not apply
- * Special Order only



For installation of all polished, polished glazed, and honed porcelain tiles, use a grout release prior to grouting and a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet, exterior, or countertop applications. Do not use acidic cleaners.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit bedrosians.com for current product information.

