

Field Tile Size



**Calacatta Oro - CAO**  
STPCL2CAO1224 - 12"x24" Pressed - Matte  
STPCL2CAO1224P - 12"x24" Rectified - Pol.



**Bianco Carrara - BIC**  
STPCL2BIC1224 - 12"x24" Pressed - Matte  
STPCL2BIC1224P - 12"x24" Rectified - Pol.



**Travertino Chiaro - TRC**  
STPCL2TRC1224 - 12"x24" Pressed - Matte  
STPCL2TRC1224P - 12"x24" Rectified - Pol.




**Travertino Grigio - TRG**  
STPCL2TRG1224 - 12"x24" Pressed - Matte  
STPCL2TRG1224P - 12"x24" Rectified - Pol.

2"x2" Mosaic (12"x12" Sheet)



**Calacatta Oro - CAO**  
STPCL2CAO22MO - Matte  
STPCL2CAO22MO-P - Polished



**Bianco Carrara - BIC**  
STPCL2BIC22MO - Matte  
STPCL2BIC22MO-P - Polished




**Travertino Chiaro - TRC**  
STPCL2TRC22MO - Matte  
STPCL2TRC22MO-P - Polished



**Travertino Grigio - TRG**  
STPCL2TRG22MO - Matte  
STPCL2TRG22MO-P - Polished

2"x6" Mosaic (12"x12" Sheet)



**Calacatta Oro - CAO**  
STPCL2CAO26MO - Matte  
STPCL2CAO26MO-P - Polished



**Bianco Carrara - BIC**  
STPCL2BIC26MO - Matte  
STPCL2BIC26MO-P - Polished










**Travertino Chiaro - TRC**  
STPCL2TRC26MO - Matte  
STPCL2TRC26MO-P - Polished



**Travertino Grigio - TRG**  
STPCL2TRG26MO - Matte  
STPCL2TRG26MO-P - Polished

## SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		STPCL2***1224	12"x24"	Non-Rectified Field Tile - Matte	8	15.75
		∅ STPCL2***1224P	12"x24"	Rectified Field Tile - Polished	8	15.75
Trim		STPCL2***312BN	3"x12"	Bullnose - Matte	15	3.63
		∅ STPCL2***312BN-P	3"x12"	Bullnose - Polished	15	3.63
Mosaic		∅ STPCL2***22MO	12"x12" Sheet	2"x2" Mosaic - Matte	-	-
		∅ STPCL2***22MO-P	12"x12" Sheet	2"x2" Mosaic - Polished	-	-
		∅ STPCL2***26MO	12"x12" Sheet	2"x6" Mosaic - Matte	5	-
		∅ STPCL2***26MO-P	12"x12" Sheet	2"x6" Mosaic - Polished	5	4.90

## ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 350 lbf	≤ 0.5%	Unaffected

## APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻

## LEGEND

- Product rated for Interior & Exterior use
- Applications & ANSI Technical Specifications do not apply
- Product rated for Interior use only
- \* Special Order only
- † May be suitable for Exterior Floors



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COM/IGG UL 2918

For installation of all polished, polished glazed, lappato, and honed porcelain/ceramic tiles, use a grout release prior to grouting to prevent absorption of the grout into the tile's micropores. Use a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the polished or honed tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet, exterior, or countertop applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

