VyLuxe®

Sizes



White 100002180 - 7"x48" SPC Vinyl



Tan 100002179 - 7"x48" SPC Vinyl



Beige 100002177 - 7"x48" SPC Vinyl



Grey 100002178 - 7"x48" SPC Vinyl

Quarter Rounds

Quarter Rounds molding is used with baseboards and can be useful to cover gaps where baseboard meets the floor.







Tan 100000639



Beige 100000357



Grey 100000358



Stair Nose

Stair Nose molding is used to protect the edges of the treads of your stairs. They minimize the scuffs, scratches and stains that mar the surface. They take the brunt of the wear and tear and prolong the life span of your stairs, therefore, minimizing your maintenance costs.



White



Tan 100002183



Beige 100002181



Grey 100002182



Reducer Molding*

Reducer Molding is used when two floors of slightly different thicknesses come together, such as laminate floor and a wood, vinyl, ceramic or low-pile carpet floor.

*Must purchase U-Track to install Reducer Molding (100000359)



White 100000337



100000637



Beige 100000339



100000340



T-Molding*

T-molding is used as a bridge between two floors of approximately equal height, especially used in doorways without thresholds. T-Molding are also used to provide expansion joints when a floor dimension exceeds the length or width of 40'.

*Must purchase U-Track to install T-Molding (100000359)



White 100000328



Tan 100000636



Beige 100000330



Grey 100000331





SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Plank		100000•••	7"x48"	$SPC\ Vinyl-22\ Mil\ Wear\ Layer\ with\ UV\ Cured\ Polyure thane\ \&\ Ceramic\ Bead\ Finishes$	10	23.75
Trim		100000•••	94.5"x1.0"x0.59"	Cassio Quarter Round 94.5" x 1.0" x 0.59"	-	-
		100000•••	94.5"x4.5"x0.59"	Cassio Flush Stair Nose 94.5" x 4.5" x 0.94"	-	-
		100000•••	94.5"x1.7"x0.28"	Cassio Reducer 94.5" x1.7" x 0.275"	-	-
		100000•••	94.5"x1.7"x0.28"	Cassio T-Mold 94.5" x 1.7" x 0.275"	-	-
		100000359	94.5" x .047" x 0.16"	Madera/Cassio Plastic U Track 94.5" x .047" x 0.16"	-	-

TECHNICAL SPECIFICATIONS

Standard	Description	Result
ASTMF-386	Total Thickness	6.0 mm
ASTMF-410	Wear Layer Thickness	0.5 mm (22 mil)
ASTME-648	Critical Radiant Flux	ClassI
ASTMF-925	Chemical Resistance	No Change in 24 Hours
ASTMF-970	Static Load Limit	1,500 p.s.i.
ASTM F-1514	Heat Stability	< 8.0 Delta E (Pass)
ASTM F-1515	Light Stability	< 8.0 Delta E (Pass)
ASTM F-1914	Residual Indentation	< 0.002"
ISO 23999	Size Change	Pass
ASTM F-2421	Size & Squareness	< 0.25%
ASTM D-2047	Static Coefficient of Friction	Meets or Exceeds 0.6 Dry
ISO 23999	Cupping/Curling	≤ 0.1 mm
ASTME-492	Impact Sound Transmission (IIC)	IIC 63
ASTME-90	Airborne Sound Transmission (STC)	STC53
ASTM E-2179	Impact Sound Reduction (ΔIIC)	ΔIIC 24
Performance	Scratch/Scuff Resistance	Excellent
Warranty	Residential	Lifetime
Warranty	Commercial	10 Years

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•					
Commercial	•					

LEGEND

Product rated for Interior & Exterior use

- Product rated for Interior use only
- † May be suitable for Exterior Floors
- * Special Order only

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Product is subject to variation in color/shade, size, texture, and finish. Blend product from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the packaging for installation guidance. We reserve the right to make product changes at any time without notice.



LAYING PATTERNS

30% Offset

50% Offset

Random