

12"x24" Pressed Field Tile - Matte




White
100005490



Clay
100005488



Steel
100005489



Black
100005487

24"x24" Pressed Field Tile - Matte




White
100005494



Clay
100005492



Steel
100005493



Black
100005491

24"x48" 2cm R11 Paver - Matte



White
100007086



Clay
100007087



Steel
100007088



Black
100007089

2"x2" Mosaic - Matte (12"x12" Sheet)




White
100006320



Clay
100006318



Steel
100006319



Black
100006317



Area 51

Glazed Porcelain

Photo Features 24"x48" 2cm R11 Paver - Matte in White.


SIZING & PACKAGING

Type	Shape	Black Item Code	Clay Item Code	Steel Item Code	White Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		100005487	100005488	100005489	100005490	12"x24"	Pressed Field Tile - Matte	8	16.00
		100005491	100005492	100005493	100005494	24"x24"	Pressed Field Tile - Matte	4	16.00
		100007089	100007087	100007088	100007086	24"x48"	2cm R11 Paver - Matte	-	-
Mosaic		∅ 100006317	100006318	100006319	100006320	12"x12" Sheet	2"x2" Mosaic - Matte	5	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	6	≥ 400 lbf	≤ 0.5%	Unaffected


Shade Variation



V2-Slight


APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	◻	◻	● †	◻	◻
Commercial	● †	◻	◻	● †	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

