


Rectified Field Tile - Matte



**White**  
100001945 - 24"x48" Field Tile  
100001950 - 24"x48" R11 Field Tile  
100001955 - 32" x32" Field Tile




**Crème**  
100001942 - 24"x48" Field Tile  
100001947 - 24"x48" R11 Field Tile  
100001952 - 32" x32" Field Tile



**Almond**  
100001941 - 24"x48" Field Tile  
100001946 - 24"x48" R11 Field Tile  
100001951 - 32" x32" Field Tile



**Pearl**  
100001943 - 24"x48" Field Tile  
100001948 - 24"x48" R11 Field Tile  
100001953 - 32" x32" Field Tile



**Taupe**  
100001944 - 24"x48" Field Tile  
100001949 - 24"x48" R11 Field Tile  
100001954 - 32" x32" Field Tile

24"x48" Cannatte Deco - Matte



**White**  
100001960



**Crème**  
100001957



**Almond**  
100001956



**Pearl**  
100001958



**Taupe**  
100001959

4"x4" Mosaic - Matte (12"x12" Sheet)



**White**  
100002864



**Crème**  
100002861



**Almond**  
100002858



**Pearl**  
100002862



**Taupe**  
100002863



# Thaddeus

## Glazed Porcelain

Photo Features 24"x48" Rectified R11 Field Tile - Matte in Crème.


### SIZING & PACKAGING

Type	Shape	Almond Code	Crème Code	Pearl Code	Taupe Code	White Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		100001941	100001942	100001943	100001944	100001945	24"x48"	Rectified Field Tile - Matte	2	15.50
		100001946	100001947	100001948	100001949	100001950	24"x48"	R11 Anti-Slip Rated Rectified Field Tile - Matte	2	15.50
		100001951	100001952	100001953	100001954	100001955	32"x32"	Rectified Field Tile - Matte	2	13.77
Deco		100001956	100001957	100001958	100001959	100001960	24"x48"	Rectified Cannatte Deco - Matte	2	15.50
Trim		100002865	100002866	100002867	100002868	100002869	3"x24"	Bullnose - Matte	10	-
Mosaic		∅ 100002858	100002861	100002862	100002863	100002864	12"x12" Sht. 4"x4" Mosaic - Matte		5	-

### ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	Pass ≤ 175 (ISO)	Unaffected	N/A	Pass (1,300 ISO)	≤ 0.5%	Unaffected

### Shade Variation



### ANSI TECHNICAL SPECIFICATIONS - R11

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	Pass ≤ 175 (ISO)	Unaffected	8	Pass (1,300 ISO)	≤ 0.5%	Unaffected

### APPLICATIONS



	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻

### APPLICATIONS - R11

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	◻	◻	◻	◻	◻	◻
Commercial	◻	◻	◻	◻	◻	◻

### LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- \* Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

100002979  
REV: 5/2022

[bedrosians.com](http://bedrosians.com)

