

3IN Wall Mount Downlight Cylinder

Wall mounted • Wet location listed



Specifications:

- Graphite (-143) (painted)
- Aluminum Construction
- Clear glass lens
- 3" LED wall mount downlight cylinder
- This sleek, contemporary cylinder is ideal for indoor or outdoor applications
- A Graphite finish complements a variety of exteriors
- Warm white, 3000K, color temperature, 90 CRI
- 907 lumens, 75 lumens per watt (delivered)
- Die Cast Aluminum construction with durable powder coated finish
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	12w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	907/75 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	5 year warranty
Labels	CSA Wet location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

Images:



Dimensions:

Width: 4-1/2"
 Depth: 5-1/2"
 Height: 5-5/8"
 H/CTR: 3"

3IN Wall Mount Downlight Cylinder

Wall mounted • Wet location listed



Photometrics:

ELECTRICAL DATA

Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.102 A
Input Power	12
Power Factor	
THD	<20%
FCC	FCC Title 47, Part 15, Class B
Operating Temperature	-10 °C to 40 °C
Dimming	Yes*

*See Dimming Notes for more information

P563000-143-30K


LED Light Engine: 3000 K 90 CRI
 System Wattage: 12
 Fixture delivered lumens: 907
 Fixture Efficacy: 75
 Spacing Criteria: 1.3

CANDELA DISTRIBUTION

DEG	CANDELA	LUMENS
0	446	
5	446	42
15	433	122
25	405	186
35	351	218
45	238	183
55	113	103
65	38	40
75	10	12
85	1	1
90	0	

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%FIXT
0-30	351	38.7
0-40	569	62.7
0-60	855	94.2
0-90	907	100.0
90-180	0	0.0
0-180	907	100.0



Test Date **09/28/17**



Dimming Notes:

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron DVELV-300P

Lutron Caseta Wireless

Leviton 6672

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.