

One-Light Outdoor

Project:			
Fixture Type:			
Location:			
Contact:			

Wall mounted · Wet location listed

Specifications:

- · Antique Bronze (-20) (powder coat paint)
- · Die cast and extruded aluminum Construction
- · Die-cast aluminum construction with durable powder coated finish
- · 788 lumens 46 lumens/watt
- · 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- · Mounting plate for outlet box included
- · 6" of wire supplied
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	1			
Input Power	16.9w			
Input Voltage	120 V			
Input Frequency	60 Hz			
Lumens/LPW (Delivered)	537/31.7 (LM-79)			
CCT	3000 K			
CRI	90 CRI			
Life (hours)	60,000 (L70/TM-21)			
FCC	FCC Title 47, Part 15, Class B			
Min. Start Temp	-30 °C			
Max. Operating Temp	30 °C			
Warranty	5 year warranty			
Labels	cCSAus Wet location listed			
	Meets California Title 24 high efficacy requirements			
	for outdoor use only			

Images:



Dimensions:

Width: 5" Depth: 8" Height: 7-1/2" H/CTR: 2-1/2"



One-Light Outdoor

Wall mounted · Wet location listed

Photometrics:

ELECTRICAL DATA

Input Voltage 120 V
Input Frequency 60 Hz

Input Current

 Input Power
 16.9

 Power Factor
 0.929

 THD
 <20%</td>


FCC FCC Title 47, Part 15, Class B

Operating Temperature -30 °C to 30 °C

Dimming Yes*

LED Light Engine: 3000 K 90 CRI

System Wattage: 16.9
Fixture delivered lumens: 537
Fixture Efficacy: 31.7
Spacing Criteria: 1



DEG	CANI	DELA	LUMENS
	0.0		
0	430		
5	430	41	
15	409	114	
25	311	142	
35	193	121	
45	104	81	
55	35	32	
65	6	6	
75	1	1	
85	0	0	

90

CANDELA DISTRIBUTION

ZONAL	LUMEN SUMI	MARY
ZONE	LUMENS	%FIXT
0-30	297	55.2
0-40	418	77.8
0-60	531	98.8
0-90	537	100.0
90-180	0	0.0
0-180	537	100.0

^{*}See Dimming Notes for more information



One-Light Outdoor

Wall mounted · Wet location listed

	۰						B 1		
I)	п	m	m	п	n	α		വ	es
\boldsymbol{L}	ш		ш	ш	ш	=	1.4	ıvı	LC3

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P

Lutron Nova NTELV-300

Lutron Vierti VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton AWRMG-EAW

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.