ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: Turn off the main power at circuit breaker before installing fixture. AVERTISSEMENT: Coupez la source d'alimentation principale au panneau central de disjoncteurs avant d'installer le luminaire.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements.

2. READ AND SAVE THIS INSTRUCTIONS.

Outlet Box Hardware Package (included): House Ground Wire Wire Connector (C) \bigcirc Fixture Wire Mounting Strap Unit (A) Mounting Screw (B) Wire Connector (C) Bolt Nut (D) Rubber Pad (E) Mounting Strap Unit (A) Fixture Mounting Screw Green Ground Screw Mounting Screw (B) Installation Steps Fixture Ground Wire Canopy Turn off the power at fuse or circuit box. Rubber Pad (E) Bolt Nut (D) 1. Attach the mounting strap unit (A) to the outlet box by using two mounting screws (B). Socket 2. Pull out the source wires from the outlet box. Make wire connections using wire connectors (C) as follows: Connect the hot wire (usually black insulation) from the fixture to the black wire from the power source. Connect the neutral wire (usually white insulation) Shade from the fixture to the white wire from the power source. • Attach the fixture ground wire (usually green insulation or bare wire) to the mounting strap unit (A) with the green ground screw. Then, depending on local code, then connect it to the house ground wire with the wire connector (C). Carefully put all of the wires back into the outlet box. Socket Ring 3. Attach the canopy to the mounting strap unit (A) by inserting the fixture mounting screws, and then secure it with two rubber pads (E) and two bolt nuts (D). Max.60W Type A Bulb

Turn on the power at fuse or circuit box.

or packaging for maximum wattage allowed.

4. Attach the shade to the socket, then secure it with the socket ring.

5. Install the bulb (not included). Check relamping label at socket area



(not included)

The following parts are available for re-order if damaged or missing.



