


# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

**NOTE:** 1. Before installing, consult local electrical codes for wiring and grounding requirements.  
2. Read and save these instructions.

## Hardware Package (included):




## Installation Steps

Turn off the power at fuse or circuit box





1. Attach the mounting strap unit (A) to the outlet box by using two mounting screws (B).
2. Pull out the source wires from the outlet box. Make wire connections using wire connectors (C) as follows:
  - Connect the hot wire (black insulation) from the power source to the black wire from the fixture.
  - Connect the neutral wire (white insulation) from the power source to the white wire from the fixture.
  - Attach the fixture ground wire (bare wire) to the mounting strap unit (A) with the green ground screw, or connect to the source ground wire if available.Carefully put the wires back into the outlet box.
3. Install 3 x 60W Max. candelabra base bulbs (not included). See relamping label at socket area or packaging for maximum wattage allowed.
4. Attach the fixture onto the mounting strap unit (A) and tighten it with two bolt nuts (D).


Turn on the power at fuse or circuit box



The following parts are available for re-order if damaged or missing.

**Spare Parts List:**

				→ Mounting Hardware 6630MM (1SET)
Mounting plate Unit (A)	Mounting Screw (B)	Wire Connector (C)	Bolt Nut (D)	



1 Year Warranty