

ASSEMBLY AND INSTALLATION INSTRUCTION

WARNING: SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER!

NOTE: BEFORE INSTALLING, CONSULT LOCAL ELECTRICAL CODES FOR WIRING AND GROUNDING REQUIREMENT.

Installation Steps:

1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Outlet Box.
 2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
 3. By measuring, determine correct distance hole in mounting plate, then drilled two holes (by measuring distance hole) in the wall at outlet box of side; raise the plastic anchor insert the hole. Attach the mounting plate to the outlet box with two outlet box screws and two wood screws as shown, tighten screws securely with the screwdriver. The side of the mounting plate marked "GND" must face out. **The outlet box is not included.**
 4. Guide supply wires through hole in center of mounting plate.
 5. **Follow wiring instructions carefully:**
Connect the White Fixture Wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire. Make sure all Wire Connectors are secure and do not easily pull off with the slight tug. Connect Ground Wire from the Outlet Box and Fixture Ground Wire to the Mounting plate with the Green Grounding Screw provided. Tuck the wire connections neatly into the wall outlet box.
 6. Place the backplane over the mounting plate, aligning the backplane holes with screw hole of the mounting plate on side, then lock it securely with mounting screws.
 7. Raise the glass shade insert to the slot of lamp holder, aligning the reverse side holes with the backplane's thread holes, lock it securely with the handle screws.
 8. Install the light bulbs in accordance with the fixture's specifications.
- NOTE: DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
9. Your installation is now complete. Return the power to the Outlet Box and test the fixture.

