

Manually extend the glass visor to activate the fan and lighting.

Quick release, dishwasher-safe, stainless steel with mesh grease filters ensure a clean, fresh kitchen. Heat Sentry[™] detects excessive heat and adjusts speed to high automatically.

10-minute time-delay shut-off feature and reminder light for filter maintenance.

Charcoal filter kits are available when recirculating air into the

kitchen is desired (duct work

CFM Reducer Kit for internal blower reduces max CFM to 250–300.

Works with optional Universal Make-Up Air Dampers.

Model Numbers


U10236BLI U10230SBE

Hood Sizes

U10230BLI U10236SBE U10230SBI U10242SBE U10236SB



The U102 features electronic 4-speed pushbutton controls with an easy-to-read blue digital display.



Widths 30", 36", 42" Depth 12-3/4"-18-1/2" Finish Stocked Brushed Stainless Steel, Powdercoat Black Special Order Not Available **Features** Halogen, G4-20W Lighting Type 2 Number of Lamps 2 Lighting Levels Lighting Lamps Included Yes Control Type 4-speed Pushbutton Control Features Heat Sentry[™], Delay Off, Filter Timer Remote Control Not Available Stainless Steel with Mesh Filter Type Grease Filter

Hood Blower Included (U102I)

Non-ducted Capability

Internal		
Blower CFM	500	
Sones	10.0	

Hood Blower Options (U102E blowers sold separately)

External In-line	ILB3	ILB6	ILB9	ILB11	
Max CFM	280	600	800	1100	
Sone levels are typically half of comparable CFM internal blowers.					
71 7					
External Exterior	EB6	EB9	EB12	EB15	
	<u>-</u>	EB9 900	EB12 1200	EB15 1500	

Accessories

Non-ducted Recirculating Kit ANKU10

Universal MUA Damper MD6TU, MD8TU, MD10TU

CFM Reducer Kit ARP8

Installation Requirements

Amps @ 120V 3


Electrical Direct Wire

Duct Size: Internal Blower 8"

Duct Size: External Blower 8" at hood (Transition to 10"

typical, see pages 64-65)

Duct Direction Vertical
Backdraft Damper Included



Installation height above the cooking surface: 22-1/2"-30"

Not recommended for use with gas or electric grills

For more details see the product specifications sheet found at www.BESTRangeHoods.com