

Product details

CLIP top thick door hinge 95°, full overlay application, hinge cup: INSERTA



| | |
|----------------------------|---------------|
| Part number | 71T9590B |
| Item number | 06914383 |
| Color / finish | Nickel-plated |
| Packaging quantity | 250 |
| Weight per 1,000 Pcs in kg | 94.92 |
| EAN code | 9002617648096 |
| UPC code | |

Technical attributes

| Attribute | Value |
|--|--|
| application | thick door hinge |
| cranking | full overlay application |
| opening angle | 95 |
| closing mechanism | with spring |
| hinge version | for BLUMOTION 973A |
| cover cap type | rectangular, horizontal, center mounting |
| cover cap type | With rectangular chamfer and off-center mounting |
| hinge cup material | Steel hinge cup |
| hinge cup finish | Nickel-plated |
| hinge cup assembly | INSERTA |
| Flange width | 65 |
| Flange length | 23 |
| Flange height | 7 |
| diameter hinge cup boring | 35 |
| diameter of mounting holes | 8 |
| distance between borings | 45 |
| eccentric location of mounting holes to hinge cup hole | 9.5 |
| cup boring depth | 12.6 |
| minimum boring distance | 3 |
| maximum boring distance | 7 |
| arm material | Steel |
| arm finish | Nickel-plated |
| collision measurement (hinge arm height) | 22 |
| fixed dimension / factory setting | 11 |
| type of side adjustment | With screw |
| Side Adjustment | +/- 2 mm |
| type of depth adjustment | convenient with spiral screw |
| Depth adjustment | plus 3/minus 2 mm |
| reveal | 1.5 |
| item package | 1 piece |
| packaging | industrial packing |