


RDM2 RADIATION DAMPER FOR VENTILATION FANS



Radiation damper for use with Broan and NuTone ventilation fans (sold separately).

FEATURES

- For use in 1, 2 and 3 hour rated floor-ceiling and roof-ceiling constructions
- Galvanized steel frame
- High temperature, non-asbestos, reinforced fiber thermal fabric
- Stainless steel closure springs
- 165°F fusible link
- Separate outer frame allows complete fan and damper serviceability without disturbing the surrounding ceiling material
- Includes light jumper cable
- Meets or exceeds NFPA-90A
- UL Classified (UL-555C)

RDM2 for use with the following ventilation fan models:

Broan A110-B, A80-B, A80HD-B, AE110-B, AE110L-C, AE50-B, AE80B-B, AE80BL-D, AE80S-B, AE80SL-C, AE110S-B, AE110SL-C, A110F1, A80F1, AE100BF1, AE110F1, AE50F1, AE80BF1, AE80BLF1, AE50110DC, AE50110DCL, AE50110DCS, AE50110DCSL, AE50110DCF, AE50110DCLF, A000HFNF, A000HFKT, A000HSNF, A000HSKT, A000HLNF, A000HLKT

NuTone AEN110-B, AEN110L-C, AEN50-B, AEN80B-B, AEN80BL-D, AN110-B, AN80C-B, AEN110F1, AEN80BF1, AN000HFNF, AN000HFKT, AN000HSNF, AN000HSKT, AN000HLNF, AN000HLKT


TYPICAL SPECIFICATION

Radiation damper shall be Broan/NuTone RDM2 suitable for use with the following ventilation fan models:

Broan A110-B, A80-B, A80HD-B, AE110-B, AE110L-C, AE50-B, AE80-B, AE80B-B, AE80L-C, AE80BL-C, AE80S-B, AE80SL-C, AE110S-B, AE110SL-C, AE50110DC, AE50110DCL, AE50110DCS, AE50110DCSL

NuTone AEN110-B, AEN110L-C, AEN50-B, AEN80-B, AEN80B-B, AEN80L-C, AEN80BL-C, AN110-B, AN80C-B

Radiation damper shall be rated for use in up to three hour ceiling constructions. It shall be UL Classified (UL-555C) and meets or exceeds NFPA-90A.



SEE DETAILS ON
UL CLASSIFICATION
MARKING ON PRODUCT

Broan Hartford, Wisconsin www.broan.com www.nutone.com 800-558-1711
Venmar Ventilation ULC Drummondville (Quebec), Canada www.broan.ca www.nutone.ca 877-896-1119

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date