

Chimney

BWS2 SERIES

This sleek low-profile design is the perfect statement for today's kitchens. Available in stainless steel and black stainless-steel finishes. Bright LED lighting enhances your cooking experience, while the 3-speed backlit soft touch control makes operation easy.

SIZE STAIN		INLESS BLACK STAINLESS			GREASE FILTERS (replacement)			NON-DUCTED CHARCOAL FILTERS		
29-1/2 in.	BWS23045	SS BWS	BWS2304BLS		S9910487 (set of 2		FILTERBWPTS (set of 2)			
IVI PERFORMAI	NCE									
				Sones			(CFM		
Duct Orientati		Damper	Normal		High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w	
Round - Vertical	6 in.	Included	3.0	5.5	8.5	240	350	385	400	
EATURES										
lax Blower Airflo	w 450 CF	450 CFM				-				
inish	430 Sta	430 Stainless Steel no. 4 Brushed								
Vall Mount	Il Mount Yes									
elescopic Flue	Yes - Ac ceilings	Yes - Accomodates 8-ft. to 9-ft. ceilings								
Convertible to on-ducted opera		Yes - Non-Duct Kit ARKBWS sold separately			-					
		Centrifugal								
Cord-connected	Yes									
Control type	 Blow Blow Light 	ich er low speed er medium spe er high speed : on-off nute delay	eed			-				
ighting		Modules 5.5						*		
Grease Filters	dishwas	affle filters, her-safe with lease latch			1					
AC INPUT										
20 V, 60 Hz - 2.	6 AMPS				-	Anter a state of the state of t				
OPTIONAL ACCI	ESSORIES (s	old separately	y)		A STREET					
lue Extension or 10-ft. ceiling	AEBWS AEBWS steel)	(stainless stee BLS (black sta	el), iinless			12-		10-3/4		
Jon-Duct Kit	ARKBW	'S								
MOUNTING HEIGHT					+	-				
		fhood								
4-in. from cookt								Dime	nsions	
	NIY							-	n inches.	
-year See installation n	anual for full v	varrantv tevt)			-3/4					
					Min. 23-3/4 Max. 43		$\langle \rangle$			
					ĭĭ ŭ,		\uparrow			
			ertical High Speed, in. round							
2.5										
2.0					23-3/4	_	<u>(19</u>)			
1.5						6-3/4				
1.0					- 3-3/4	6			3/8	
0.5			\searrow		+	\checkmark				
0 50 100	150 200	250 200 25	0 400	450				00000		
	150 200 Airflow (250 300 35 cfm)	0 400	450	-	19-11/16	\searrow	29-1/2		
							-			

W on laboratory measurements. CERTIFIED * Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

Intertek