Bruck By Ledra Brands Inc.

CONTACT ORDERING CODE RENATA MEDIUM Canopy, Track **LED E26**

DESCRIPTION

WEP Light (Wood Ecological Project) is designed, handcrafted in Argentina and assembled in the USA. A two-sided wood veneer section is fused with a malleable center panel for strength and flexibility to create a work of art in a variety of styles and sizes. A plethora of colors for interior and exterior of the shade are offered. Acoustic WEP lights are offered in multiple shapes and sizes and are NRC rated by a third-party lab for absorption efficiency. The natural recycled wood in many finish options, is complimented by a natural Argentinian lamb's wool inner shade for superior absorption. Factory assembly for most shades. Due to hand-crafted nature, colors vary from fixture to fixture and from photo.

HOUSING

- Sustainable, recycled, reconstructed wood veneer
- Factory assembled shades with some exceptions due to size

MOUNTING

- Renata 56: Bayonet canopy with 108" cord, field adjustable
- Renata 80: Air craft cable suspension with black canopy and 108" black cord, field adjustable.
- Optional track mounting options: Global Trac Systems, GEO track, ECO track / HALO® Power Trac track, and Zonyx track.
- Renata 56M: 4.51 lbs.
- Renata 80M: 7.72 lbs.

LISTINGS

- ULus listed to UL1598 (suitable for indoor use and dry locations only)
- cUL listed to CSA C22.2 #250.0

ORDERING CO	LM-79		
SERIES	WEP	wood shade	
TYPE	REN	renata	
SIZE	56M 80M ³	56 medium pendant, 1 x light source 80 medium pendant, 1 x light source	
LIGHT SOURCE	LLED LE264	LED, 1000 Im E26 socket	
сст	30K 35K 3018 Not applicable to	3000K, standard white LED 3500K, standard white LED 3000K, dim to 1800K, warm dim LED LE26 option. Do not include in LE26 ordering code.	
CRI	90¹ 95² Not applicable to	90 CRI, standard white 95 CRI, warm dim LE26 option. Do not include in LE26 ordering code.	
MOUNTING OPTION	PBK PMC PWH ECOBK ECOMC ECOWH GEOBK GEOMC GEOWH ZONMC	canopy, black with black cable canopy, matte chrome with black cable canopy, white with white cable ECO/HALO black with black cable ECO/HALO matte chrome with black cable ECO/HALO white with white cable GEO black with black cable GEO matte chrome with black cable GEO matte chrome with black cable GEO white with white cable Zonyx matte chrome with black cable	
OUTER SHADE COLOR	ASH BCH BLU EBY GRN GCH PGR PTB RED RCS TRC WHT YLW LPT VLT	ash beech blue ebony green grey oak ocher pale green petiribi red rose teracotta white wenge yellow light petrol violet	
INNER SHADE COLOR	ASH BCH BLU EBY GRN GYO OCH PGR PTB RED ROS TRC WNG YLW LPT VLT	ash beech blue ebony green grey oak ocher pale green petiribi red rose teracotta white wenge yellow light petrol violet	

ORDERING CODE

Follow the steps to specify your fixture, example: WEP - REN - 56M - LLED - 30K - 90 - PBK - PTB - ASH

- NOTES
 1. 90 CRI for standard white only.
 2. 95 CRI for warm dimming only.
 3. 80M available in PBK and PWH mounting only.
 4. 15W E26 socket available, use base option code LE26-15.

COLOR OPTIONS





LIGHT SOURCE


Light Source	LLED - Static White LED	LLED - Warm Dim LED	LE26 - E26 Socket
Performance			
LED	Cree CMT 1420	Luminus CDM-9	Lamp Dependant
Lumens	1150 lm	850 lm	
CCT	3000K or 3500K	3000K to 1800K	
SDCM	2-Step MacAdam Ellipse	3-Step MacAdam Ellipse	
CRI	>90	>95	
Lumen Maintenance	L90 > 41,500 hours	L70 > 54,000 hours	
Technical Specs			
Socket Listing	Integrated LED module	Integrated LED module	Medium E26 base socket
	ETLus Listed to UL1598	ETLus Listed to UL1598	ETLus Listed to UL1598
	(Suitable for dry locations only)	(Suitable for dry locations only)	(Suitable for dry locations only)
	cETL Listed to CSA C22.2 #250.0	cETL Listed to CSA C22.2 #250.0	cETL Listed to CSA C22.2 #250.0
	I	I	I
Mounting			
Canopy	120-277Vac, 50/60Hz input	120-277Vac, 50/60Hz input	120Vac input
	14.3W, 14.9VA	15.6W, 16.1VA	100W, 100VA (max 100W lamp)
	Tri-mode dimming (Triac, ELV and 0-10V)	Tri-mode dimming (Triac, ELV and 0-10V)	Dimmable (with compatible lamp)
	I	I	I
Warranty			
	5 year limited fixture warranty	5 year limited fixture warranty	1 year limited fixture warranty


CCT AT LIGHT LEVEL (%LF) FOR WARM DIM LED

%LF	ССТ
100%	3000
50%	2800
25%	2300
10%	1900
5%	1800


WARM DIM DIMMING CURVE

CCT RANGE: 3000K TO 1800K





RENATA 56M



RENATA 80M