

PREP PULL-OUT KITCHEN FAUCET


Features


- Solid brass construction
- 360 rotating spout
- One button operation brass sprayhead has dual function aerated or spray mode with quiet polymer-braided hose
- Spray jets have easy-to-clean surface that withstands mineral build-up
- Ceramic disc cartridge
- 1.8 gpm (6.8 L/min) max flow rate
- Over 30 finishes including 15 PVD finishes

Codes/Standards Applicable

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B1Ž5.1
- NSF 61 and NSF 372





XX = DENOTES HANDLE STYLE

DIMENSIONS (in.)					THROUGH-HOLE SPECIFICATIONS
XX HANDLE	Α	В	С		<u>MIN</u> <u>RECOMENDED</u> <u>MAX</u> Φ1-1/4" Φ1-3/8" Φ1-3/8"
ST	$6\frac{7}{8}$	3 ¹⁵ / ₁₆	3 7 16		
BST	6 7	3 ¹⁵ / ₁₆	3 7 16		8\frac{1}{4}" \rightarrow \rightarrow
FB	7 <mark>1</mark>	4 1 8	3 ¹³ / ₁₆		
BFB	7 4	4 1/8	3 <mark>13</mark>		
	(WI	1	X CER)	3 1 16"	$6\frac{3}{8}$ $12\frac{7}{16}$ $4\frac{1}{4}$ 0 0 0 0 0 0 0 0 0 0
	(LES	2 3 " MA SS SPA	X CER) ₋	3 7 / ₁₆ "	2\frac{1}{4}" \rightarrow \frac{1}{18"}
		1		2 1 / ₈ "	2\frac{1}{4}"
					3/8" COMPRESSION FITTING