

## PULL-DOWN KITCHEN FAUCET-LOW SPOUT

### Features

- 360° rotating spout with pull down sprayer
- Magnetic docking secures sprayhead into spout
- One button brass spray head has dual function aerated or spray
- Spray jets have easy-to-clean surface that withstand mineral build-up Quiet polymer-braided hose with rotating joint at sprayhead allows for smooth and non-binding use
- Ceramic disc cartridge
- Max flow rate: 1.8 gpm Solid brass construction
- Over 30 finishes including 15 PVD finishes


### Codes/Standards

Meets or exceeds the following:

- ASME A112.18.1/CSA B125.1 NSF 61 and NSF 372 CEC/DOE

- ADA compliant

# CF-K51-102-XX



CF-K51-102-FB shown

XX = DENOTES HANDLE STYLE

DIME	NSIO	NS (in.	)			H-HOLE SPECI	
XX	Α	В	С			RECOMENDE	
HANDLE				L	Ø 1-1/4"	Ø 1-3/8"	Ø 1-3/8"
FB	$7\frac{1}{4}$	4 <del>8</del>	3 <del>13</del> 16				
BFB	$7\frac{1}{4}$	4 <del>1</del> 8	3 <del>13</del> 16	<del> </del> 10 <sup>7</sup> / <sub>8</sub> " −−−−		ı	
ST	$6\frac{7}{8}$	3 <mark>15</mark>	3 <del>7</del> 16	108	•		
BSST	67/8	3 <sup>15</sup> / <sub>16</sub>	3 <del>7</del> 16				
				- B			15 7 "
				9 3 16"	-		15 7/16"
				5° C -		}	
				$7\frac{9}{16}$			
(\	1 <u>5</u> WITH	" MAX SPAC	ER)	$\frac{1}{3\frac{1}{16}}$ " $\phi 2\frac{3}{16}$ "			
(1	2 <u>5</u> 16 LESS	SPAC	( ER)	3 <del>7</del> 7 16"	-	<del>-</del>  -	17 <u>15</u> "
				$\phi 2\frac{1}{4}" \longrightarrow 2\frac{1}{8}"$		<del>1</del> -	\ \{\}
				3/8" COMPRESSION FITTING		`	