

Jalama®

Widespread Lavatory Faucet

Features

- 25+ artisan finishes including 12 PVD finishes
- · All brass construction
- 1/4 turn ceramic disc cartridge(s)
- Flexible braided hoses for ease of installation
- 1.2gpm (4.5 L/min) max flow rate



3902Q 3902QK 3902QR 3902QRI 3902QH 3902QP 3902QPI

Codes/Standards Applicable

Product meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- NSF 61, NSF 372, CEC & DOE
- · EPA WaterSense
- · Commonwealth of MA















minimum [203] 7-7/16" [189] 1-1/16" 5-7/8" [27] 152 150 3-1/2" [90] 2-5/8" [66] 1-3/8" [35] min stem height for all handles 1-13/16" [47] max (2-9/16" [66] less spacer) 2-15/16" max 9/16" min [75] [14] 4-7/16" [113] 2x 3/8" compression fittings Ø2-3/16" 56 2-1/8" [54] 6-5/16" [160] Through-Hole Specifications <u>Min</u> Recommended <u>Max</u> Ø11/16" [18] Ø1-1/8" [29] Ø1-1/2" [38] Spout: Ø 1-1/4" Ø1-1/4" [32] Ø1-3/8" [35] Ø1-1/2" [38] [32] Dimensions are inches, rounded to 1/16"

Specifications subject to change without notice

[Dimensions in brackets are mm, rounded to 1mm]