

CS TrackSystems are an innovative range of track systems designed for a multitude of sliding doorway applications.

CS WallMountTrack

is suitable for surface sliding applications where there is enough strength in the wall to side mount a track system above an opening.

Installation is quick and easy as the track is supplied with premachined fixing slots. The track also comes with a pre-finished, removable aluminum fascia and end caps that neatly conceal the top of the door, track and carriage system.



CS WallMountTrack with clear anodized finish.



& WallMountTrack

Design Features & Options

Available as a single track set-up only, i.e. no double or triple track versions are available.

Track can be configured to suit Bi-Parting door

setups.



Fascia may be anodized or powder coated in a range of color options. Standard stocked finishes available: Clear or Bronze Anodized. Inquire about custom colors.

Standard CS Track Features

Our engineers focus on constantly developing new products and refining existing ones. That's why our products come with a number of unique features:

- Heavy duty one-piece 1 extruded aluminum track.
- Pre-machined mounting holes.
- Fascia is removable for future servicing requirements.
- Minimal clearance means carriages/ wheels cannot jump off track or jam.
- Large diameter wheels with precision ground bearings make for smooth running.
- Radiused track reduces friction and allows dust to be pushed into the gutters so the door always slides smoothly.





M8 carriage & mounting plate with stop


- M8 body made from cast stainless steel for strength and reliability. 4-wheel carriages are standard on all doors over 200lb.
- **CarriSnap**[™] quick release system allows the door to be removed easily from track; no need to unscrew anything and lose door height adjustment.

www.cavitysliders.com

High quality products designed in New Zealand

- T (888) 466 0030 F (310) 769 5824
- E info@cavitysliders.com

Technical Information




Track Finish: Fascia Finish: **Door Thickness:** Max Door Weight: **Carriage Pack:**

See Design Features & Options 35-45mm 1-3/8" to 1-3/4"* 500lb 240kg M6 or M8

* For doors thicker than 1-3/4", please contact us for installation information

Fixing Detail



How to Order

- 1. Specify track length Available in 6, 8, 12 and 24' pre-cut lengths or can be cut down to specified length on request.
- 2. Specify door thickness
- 3. Specify finish

(fascia and end caps)

4. Choose a carriage pack (one per door) refer to Carriage Packs page

M6 (200lb) or M8 (500lb)

(includes carriages, mounting plates, T-Guide, fixing screws, adjusting wrench and installation instructions)

Cavity Sliders USA Inc.





Another quality product from:

