

Central Brass Company, Inc.
3325 S. Garfield Ave.
Commerce, CA 90040
(800) 321-8630
www.centralbrass.com

INSTALLATION

Tools:



Adjustable Wrench Power Drill Plumbers Putty Teflon Tape Rags

Model Number: 0366 Series


Warnings and Notes:

Check with local plumbing code requirements before installation.
This product should be installed by a local listed plumber.


Do not use plumbers putty on threads.

Installation Steps:


Drinking Fountain-Wallmount




(1) The 3/8" pipe thread nipple must be kept with a length of 1/2" from finished wall. Apply Teflon tape at the thread end of pipe nipple stretch out from finished wall. Thread wall bracket to 3/8" pipe nipple and secure the wall bracket with supplied four screws.




(5) The self-close basin faucet was preset @60 PSI to shut off water, different water pressure might affect the faucet and cause it not to function properly, if need be, remove the handle cap, sleeve and Celcon Samson nut.




(2) Apply Teflon tape on both thread ends of brass nipple, thread and tighten brass nipple to wall bracket. Thread and tighten drinking fountain to brass nipple. Ensure the drinking fountain is in level position.



(6) Use wrench to adjust brass square nut, turn counterclockwise to tighten the cartridge and turn it clockwise to loosen the cartridge until the faucet functions properly then proceed to tighten the cartridge 90° more before reassembling the Celcon Samson nut, sleeve, and handle cap back in place.



(3) Apply Teflon tape to the thread end of drain adapter. Thread and tighten drain adapter to the drink fountain.



(4) Attach drain adapter to the P-trap.

Central Brass
COMPANY, Inc.

For more care information or trouble shooting inquiries about your Central Brass product, please call:
Central Brass Company, Inc. (800) 321-8630
Monday-Friday 8 AM to 8 PM EST (5 AM to 5 PM PST)
www.centralbrass.com
Apr. 24. 23