

MODEL: SEF SHUTTER MOUNT WALL FANS

SEF shutter mount fans are designed for through the wall general ventilation applications. These multi-speed, direct drive axial fans are compact, cost effective and easy to install.

DIMENSIONS IN INCHES								
MODEL	A	B	C	D	E	F	G	WT (lbs)
SEF-10	13.0	10.1	6.1	2.5	6.0	3.5	0.3	11
SEF-12	15.0	12.1	7.1	2.5	8.0	3.5	0.3	16
SEF-14	17.0	14.1	7.9	2.5	10.0	3.5	0.3	17
SEF-16	19.0	16.1	7.9	2.5	12.0	3.5	0.3	18
SEF-18	21.0	18.1	7.6	2.5	14.0	3.5	0.3	25
SEF-20	23.0	20.1	9.4	2.5	16.0	3.5	0.3	34
SEF-24	27.0	24.1	9.9	2.5	20.0	3.5	0.3	47
SEF-30	33.0	30.1	9.9	3.0	26.0	3.5	0.3	54

CONSTRUCTION

- Impeller - stamped aluminum blades
- Guard - plated steel spiral wire
- Switch - pull chain
- Junction box
- Shutter - steel frame with aluminum blades

MOTORS

- 120 VAC, single phase
- Totally enclosed, permanently lubricated, face mount
- UL/CSA approved
- Multi-speed
 - 1/12 HP - 3 speed, shaded pole
 - 1/8 HP - 3 speed, permanent split capacitor
 - 1/4 HP - 2 speed, permanent split capacitor

PROJECT				ARCHITECT					
DATE				ENGINEER					
SUBMITTED BY				CONTRACTOR					
SPECIFICATION									
FAN NO.	MODEL NO.	MOTOR HP	SPEEDS	PERFORMANCE (CFM)			AMPS (HIGH)	QTY	OPTIONAL EQUIPMENT
				HIGH	MEDIUM	LOW			