



### LT-Series Lever Functions



**6920  
Passage  
Interconnect**

Both Levers always free turning to retract latch. Rotating inside lever simultaneously unlocks deadbolt. Deadbolt also unlocked with key or by rotating interior thumb turn.



**6941 Entry/Office  
Interconnect**

Key or inside push button lock both levers. Turning inside lever unlocks both levers and the deadbolt simultaneously. "Pushing & Turning" inside push button activates the "Storeroom function". Deadbolt also locked or unlocked with key or by rotating interior thumb turn.

### LT6900-Series Interconnect Specifications

Latches	Solid Stainless Steel Bolt. 1" wide Round Corner. 2-3/8" backset standard, 2-3/4" Optional.
Strikes	1"x2-3/4" (RCS) for Deadbolt, Full Lip 2-14" for Lever Standard, Other strikes available.
Cylinder	5 pin KW1 standard. Schlage-C optional.
Door Prep	1" edge Bore, 1"-1/8" x 2-1/4" Latch mortise, 2-1/8" cross bores 4" center to center.
Door Thickness	Minimum 1-3/8", maximum 1-3/4" door thickness.
Handing	All LT6900-Series Interconnects are non-handed operation.
U.L.	Standard 3 hour U.L. Fire Rated.
BHMA	Meets ANSI/BHMA 156.2 Grade-2 ; 400,000 cycles.
ADA	Full lever return to within 1/2" of door.

