



Ball (BK)



Colonial (CK)




Egg (EK)



Available UL
LISTED

	A	B	C
Ball	1-15/16"	2-1/2"	2-5/8"
Colonial	2-3/16"	2-1/2"	2-5/8"
Egg	2-1-2"	2-1/2"	2-5/8"



Knob Specifications & Options	
ANSI / BHMA	ANSI 156.2 Grade-3. 200,000 cycles.
Rose Diameter	2-5/8"
Cylinder	KW1" 5-pin std, "C" optional.
Keying	As specified: Available Master keyed, Builder keyed, KD, KA.
Latch	Adjustable backset, 1" round corner narrow faceplate std. Square corner or drive-in adjustable latch optional.
Strike	PT-LS06: 2-3/4" full lip round corner strike std.
Door Prep	Edge bore 1", latch mortise 1"x 2-1/4", cross bore 2-1/8", backset standard 2-3/8", optional 2-3/4".
Door Thickness	Min 1-3/8", Max 1-3/4".
Handing	Non-handed.
UL Labeled	Available 20-minute UL Labeled.
Warranty	Lifetime mechanical, 5 year finish.

	In Stock Finish							Case Qty
STYLE	SS	TB	AB	AN	BC	PB	PS	Units
Ball	x	x	x	x		x	x	24
Colonial	x	x		x	x	x	x	24
Egg	x	x			x		x	24

Function	Operation
2020 Passage	Both knobs always free turning. No locking operation.
2030 Privacy	Inside turn-button locks and unlocks both knobs. Knob can be unlocked by rotating the outside privacy mechanism.
2040 Entry	Outside key or inside turn-button locks both knobs.
2090 Dummy	1/2 Dummy - Used as pull or decorative trim only.