

Product Specifications

Style Number	VV465	
Construction	Solid Polymer Core	
Edge Profile	Micro Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.13"	18.11 cm
Actual Product Length	48.03"	121.99 cm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Overall Product Thickness	0.173"	4.4 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	28.52 sq ft	2.65 sq m
Pieces per Box	12 pcs	
Weight per Box	41.89 lbs	19 kg
Boxes per Pallet	45 boxes	



2060 Whirlpool Oak

Colors





Galaxy

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I

Warranties

- 30 Years
- 7 Year Light Commercial

Certifications

GreenGuard (Certification, Gold, Private Label) Certified