![COREtec the Original logo]

Product Specifications

	US Units	Metric Units
Style Number	VV488	
Construction	Solid Polymer Core	
Edge Profile	Accent Bevel	
Nominal Dimensions	9" wide, 72" long	
Actual Product Width	9.06"	23.01 cm
Actual Product Length	72.83"	184.98 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.204"	5.2 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.047"	1.2 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	36.64 sq ft	3.404 sq m
Pieces per Box	8 pcs	
Weight per Box	61.95 lbs	28.1 kg
Boxes per Pallet	48 boxes	

2090 Hampshire Oak

Colors

2092 Manor Oak	2093 Canterbury Elm	2094 Cheshire Elm	2095 Bastion Elm
2096 Cambridge Elm	2097 Berkshire Elm	2098 Bedford Oak	2099 Southampton Oak
2100 Kent Oak	2101 Wiltshire Oak	2102 Buckingham Oak	2091A Ravenswood Oak

COREtec Pro Plus HD 9"

Performance

Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I

Warranties

USF Lifetime

USF 15 Year Heavy Commercial