COREtec®
the Original

Product Specifications

Style Number	VV024
Construction	Waterproof Foamed Core
Edge Profile	Micro Bevel
Nominal Dimensions	7" wide, 48" long

	US Units	Metric Units
Actual Product Width	7.13"	18.11 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	38.24 sq ft	3.55 sq m
Pieces per Box	16 pcs	
Weight per Box	63.05 lbs	28.59 kg
Boxes per Pallet	35 boxes	

210 Kingswood Oak

Colors

105 Dune	210 Kingswood Oak	211 Nantucket Oak	705 Ivory Coast Oak	706 Alabaster Oak
707 Blackstone Oak	708 Hudson Valley Oak	709 Olympic Pine	710 Broad Spar Oak	711 Cabin Oak
712 Amelia Oak	713 Whidbey Oak	714 Marsh Oak	715 Fidalgo Oak	716 Midway Oak

COREtec Plus Plank 7"

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Warranties

USF Lifetime

Wpc 15 Yr Com Ltd

Com Ub Bond 4100/4151

Certifications

FloorScore Certified

GreenGuard (Certification, Gold, Private Label) Certified