



COREtec Originals Premium VV810

Product Specifications

Style Number	VV810
Construction	Waterproof Foamed Core
Edge Profile	ENHANCED INTEGRATED BEVEL
Nominal Dimensions	9" wide, 72" long

	US Units	Metric Units
Actual Product Width	8.85"	22.479 cm
Actual Product Length	72.05"	183.007 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.403"	10.25 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Soft Step	
Attached Underlayment Thickness	0.138"	3.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Lock N Place Clips	
Country of Origin	Imported	

Packaging

Area per Box	26.47 ft²	2.4591 m²
Pieces per Box	6 pcs	
Weight per Box	45.57 lbs	20.67 kg
Boxes per Pallet	52 boxes	




1024 Conch Ash


Colors



1024 Conch Ash




3019 Midnight Oak



3021 Vintage Taupe Ash



4027 Cerith Oak



4028 Mist Oak



5024 Sand Dollar Oak



5025 Flaxen Ash



5026 Blonde Oak



5027 Parchment Oak



5028 Sea Salt Oak

COREtec Originals Premium VV810

Performance

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


Warranties

- USF Lifetime
- USF 10 Year Medium Commercial


Coordinating Trim




Baby Threshold*
BT7CT | 94"



T-Molding*
TM7CT | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
FS9HU | 94"

*Packaged with molding track

Stair Tread



White Riser
USC02 | 48"



Stair Tread
03Z70 | 48"
TR2CT | 48"