

Product Specifications

Style Number	VV017	
Construction	Solid Polymer Core	
Edge Profile	Micro Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.2"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.196"	5 mm
Core Thickness	0.157"	4 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	






Packaging

Area per Box	28.84 sq ft	2.67 sq m
Pieces per Box	12 pcs	
Weight per Box	48.61 lbs	22.04 kg
Boxes per Pallet	50 boxes	




1001 Chesapeake Oak

Colors

				
1001 Chesapeake Oak	1002 Galveston Oak	1003 Copano Oak	1004 Monterey Oak	1005 Belmont Hickory
Color Variation: V2 - Slight		Color Variation: V2 - Slight	Color Variation: V2 - Slight	Color Variation: V4 - Substantial
				
1008 Biscayne Oak	1012 Duxbury Oak	1016 Laguna Oak	1018 Quincy Oak	1019 Roswell Hickory
Color Variation: V3 - Moderate	Color Variation: V3 - Moderate	Color Variation: V2 - Slight	Color Variation: V2 - Slight	


COREtec Pro Classics VV017



1020 Springfield Oak




1023 Flagstaff Oak



2061 Cartwheel Oak



2062 Elliptical Oak



7037 Bakersfield Oak

Performance

Static Load (ASTM F970)	Passes (Modified), *500 lbs
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime

[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

USF 15 Year Heavy Commercial

Certifications

FloorScore Certified

GreenGuard Gold Certified

GreenGuard Gold Certified

Coordinating Trim




Baby Threshold*

BT3HU | 94"

01V20 | 94"

04Z02 | 94"




T-Molding*

TM3CT | 94"

02V62 | 94"

04Z01 | 94"




Quarter Round

QTRCT | 94"


01V46 | 94"

04Z00 | 94"



Overlap Stairnose*

01V95 | 94"



Flush Stairnose

FS4CT | 94"

02V17 | 94"

04Z05 | 94"

*Packaged with molding track



COREtec Pro Classics VV017



Stair Tread



White Riser
USC02 | 48"



Stair Tread
03Z70 | 48"