

Product Specifications

Style Number	VV674	
Construction	Mineral Core	
Edge Profile	Enhanced Painted Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.6"	19 cm
Actual Product Length	47.64"	121 cm
Overall Product Thickness	0.354"	9 mm
Core Thickness	0.315"	8 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Installation Methods	Floating	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	15.08 sq ft	1 sq m
Pieces per Box	6 pcs	
Weight per Box	37.04 lbs	16.8 kg
Boxes per Pallet	60 boxes	



3013 Ansley Walnut

Colors



COREtec Advanced 7"x48"

Performance

Static Load (ASTM F970)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


Warranties

- USF Lifetime
- 15 Year Scratch
- 20 Year Light Commercial


Coordinating Trim




Baby Threshold*
BT6NC | 94"



T-Molding*
TM6NC | 94"



Quarter Round
QTRNC | 94"



Flush Stairnose
FS8NC | 94"

*Packaged with molding track

Stair Tread



Stair Tread
03Z70 | 48"