

Product Specifications

| | |
|---------------------------|---------------------------|
| Style Number | VV820 |
| Construction | Waterproof Foamed Core |
| Edge Profile | Enhanced Integrated Bevel |
| Nominal Dimensions | 7" wide, 48" long |

| | US Units | Metric Units |
|--|--------------------|--------------|
| Actual Product Width | 7.05" | 18 cm |
| Actual Product Length | 48.03" | 122 cm |
| Wear Layer Thickness | 20 mil (0.02") | 0.5 mm |
| Overall Product Thickness | 0.393" | 10 mm |
| Core Thickness | 0.256" | 6.5 mm |
| Attached Underlayment | Attached Soft Step | |
| Attached Underlayment Thickness | 0.138" | 3.5 mm |
| Finish | UV Acrylic | |
| Installation Methods | Floating | |
| Profile | Lock N Place Clips | |
| Country of Origin | Imported | |

Packaging

| | | |
|-------------------------|------------|---------|
| Area per Box | 18.8 sq ft | 2 sq m |
| Pieces per Box | 8 pcs | |
| Weight per Box | 31.97 lbs | 14.5 kg |
| Boxes per Pallet | 55 boxes | |



1026 Wheat Oak

Colors



Warranties

USF Lifetime


COREtec Original Premium VV820

Coordinating Trim




Baby Threshold*

BT7CT | 94"



T-Molding*

TM7CT | 94"



Quarter Round

QTRCT | 94"

*Packaged with molding track

Stair Tread



Stair Tread

03Z70 | 48"