

lines of the housing flow effortlessly into an integrated light fixture. Unique structural details on the four blades offer more than distinctive looks. Form follows function to beautiful effect in Craftmade's Beacon.

## **FEATURES**

Standard, 3 Speed Reversible Motor

Downrod Mount Only

6" Downrod (Included)

Limited Lifetime Warranty

Blades Included

Integrated LED Light Source (Dimmable)

Remote & Wall Controls (Optional)

Blades Must be Mounted at Least 10' Above the Floor for Safety.

LED Specs:

Color Temp 3000K 1250 lm Lumens CRI 90

LED Module is Guaranteed for 5 Years

#### SPECS


Blade Sweep. . . . . . . . . . . . . . . . . . 48" Number of Blades . . . . . . 4 Blade Pitch......12° Motor Size (MM) ...... 153 x 12 Shipping Wt. (lbs.).....14.9 CU. FT. in Carton . . . . . . . 1.41 Energy Guide Airflow (Cubic Feet Per Minute).....5,751 Energy Guide Wattage . . . . . 52 Watts

Energy Guide Efficiency (CFM Per Watt) ......111

Energy Guide Estimated Yearly Cost\*.....\$15

# Airflow at High Speed (Cubic Feet Per Minute).....4,615

## **CEILING DROP DIMENSIONS**



A: 6" DR - 18.03" C: 7.09"

E: 411.13

B: 6" DR - 10.98" **D:** 5.79" \*DR=Downrod









∆| Brushed Polished Nickel 48" Beacon

Model . . . . . . BEA48BNK4C1
Blade. . . . . Brushed Polished Nickel

Light . . . . . . . Integrated, Frosted Glass

\*Blades Must be Mounted at Least 10'

Above the Floor for Safety.

#### AVAILABLE FINISHES

#### BLADE OPTIONS

## LIGHT KIT OPTIONS

BNK Brushed Polished Nickel

Included

Integrated

Blades Must be Mounted at Least 10' Above the Floor for Safety.

### FAN CONTROL OPTIONS

Remote and Wall Control AdaptableUCI-2000-2 See Page 432-434

