## **CRYST** RAMA



LIGHTING THE WAY FOR SIXTY YEARS

### ASSEMBLY INSTRUCTION MODEL #ACK-921-AG



### **Crystal Sets**

A. 12 Sets (1)14.5" Glass

B 12 Sets (1)6.5" Glass

MARNING:This product can expose you to Lead, which is known to the State of California to cause cancer and/or birth defects or reproductive harm.For more information go to www.p65warnings.ca.gov



All electrical components must be installed by a licensed electrician

in accordance with the National

Electric Code and the appropriate





You will need 1- Medium Base Bulb

60 Watts recommended 100 Watts Max.

USE LED BULBS FOR EXTENDED USE

The fixture is Damp rated

#### HOW TO INSTALL:

Place the fixture parts on a soft cloth-covered platform before installation of fixture.

- 1.Attach the mounting bar onto the outlet box.
- 2. Take one big check ring with the flat side up and place it over the hex nut at the top of the fixture frame.

Then take the second big check ring, with the flat side down and place it on top of the first check ring.

Feed the wire through both big check rings, the coupler, threaded pipe, and decorative rod in that order.

- 3.Secure the big check rings down with the coupler. Then screw the threaded pipe into the coupler.
- 4.Slide the decorative rod over the threaded pipe and secure all with the hex nut.Finish by placing the small check ring, flat side up over the nut.
- 5.Decide the desired hanging height and choose the correct length of rod and chain needed.
- 6.Feed the wire through the rod (the long or short) and screw the rod onto the top of the decorative rod and secure it with the loop.
- 7.Raise the fixture up to the ceiling and do the wire connection.Attach the canopy over the mounting bar and secure it with the collar ring.
- 8.Screw the threaded nipple into the harp on the bottom of the fixture body.Slide the short tube and bottom spoke over it and secure with the hex nut.Place the small check ring over the hex nut and secure it with the finial.
- 9.Starting from the bottom, hang the glass onto the fixture frame.

# CRYST®RAMA

LIGHTING THE WAY FOR SIXTY YEARS

### ASSEMBLY INSTRUCTION MODEL #ACK-921-AG



### Part Number

### Part Numbers

- A.(1)-Mounting hardware Wire Connector × 2. Mounting Bar × 1. Mounting Screw × 2. Washer × 1. Nut × 1. Threaded nipple × 1.
- B.(1)-Canopy(W5 1/8" x H3/4")-XSN921AGCAN5IN
- C.(1)-Collar Ring
- D.(1)-Collar Loop
- E.(1)-Chain(4mm×72")-XSN921AGCHA4MM
- F.(1)-Loop
- G.(2)-Small check ring ; Ø5/8"
- H.(1)-Threaded pipe ; H6 1/8"
- I.(1)-Decorative rod ; H6"-XSN921AGDECOROD6IN
- J.(1)-Coupler ; H3/4"
- K.(2)-Big check ring ; Ø3/4"
- L.(1)-Fixture body kit Ø5"Spoke ring with 6 spokes Big check ring ; Ø3/4" x2. Tube ; W3/4"×H2 1/2". Ø9"Spoke ring with 12 spokes Tube ; W1/2"×H5/8" Harp ; W3 3/4"×H8 1/4" Socket.
- M.(1)-Threaded nipple ; H2"
- N.(1)-Short Tube; W1/2"; H1 1/8"
- O.(1)-Bottom spoke
- P.(1)-Hex nut ; W5/8"
- Q.(1)-Finial
- R.(1)-Short Rod ; H6"-XSN921AGROD6IN
- S.(1)-Long Rod ; H12"-XSN921AGROD12IN