

# Bantam

## 1.5W MiniCylinder


## 1.5W MiniCube

### Surface Mount

# VLP-1001 Series

# VLP-1002 Series

### Fixture


- No visible hardware.
- Satin Aluminum finish
- Machined aluminum housing.
- Suitable for cabinets and case goods.
- NOT for recessed installation in ceilings or walls.
- 2850°K ± 100° Cree XP-E, 80 CRI
- Remote driver; Triac dimming driver available
- Multiple US patents pending 



VLP-1001-SA



VLP-1002-SA



### Photometrics

- See [www.csllighting.com](http://www.csllighting.com) for current photometric data

### Bantam

Description	Cat. No.	# of LEDs	Lumens	Wattage	Dimensions
<input type="checkbox"/> MiniCylinder	<b>VLP-1001-SA</b>	1	80 lm	1.5 W	1 <sup>5</sup> / <sub>16</sub> " dia x 1 <sup>3</sup> / <sub>16</sub> " h
<input type="checkbox"/> MiniCube	<b>VLP-1002-SA</b>	1	80 lm	1.5 W	1 <sup>5</sup> / <sub>16</sub> " x 1 <sup>5</sup> / <sub>16</sub> " h

### Drivers

Driver #	Dimming	# of fixtures each driver can operate
<input type="checkbox"/> D-121	No	1 to 10
<input type="checkbox"/> D-122	No	3 to 18
<input type="checkbox"/> D-123*	Yes/Triac	10 to 15

\* Fixtures must be wired in series when using the D-123

Project \_\_\_\_\_

Fixture Type \_\_\_\_\_

Location \_\_\_\_\_

Contact \_\_\_\_\_

Phone \_\_\_\_\_



A Division of Troy-CSL Lighting, Inc.

14508 Nelson Avenue City of Industry CA 91744 Tel: 626.336.4511 Fax: 626.330.4266 [www.csllighting.com](http://www.csllighting.com)