

---

## 120 V Powerled linear

Long runs and flexibility are the primary features of our smooth PowerLED linears. A sleek, driverless connection ensures smooth and continuous light in every application.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>6009LED</b>	9"	3 W	250 lm	300 lm	80	3000 K	120 V
<b>6009LED-4K</b>	9"	3 W	250 lm	300 lm	80	4000 K	120 V
<b>6012LED</b>	12"	4 W	330 lm	400 lm	80	3000 K	120 V
<b>6012LED-4K</b>	12"	4 W	330 lm	400 lm	80	4000 K	120 V
<b>6024LED</b>	24"	8 W	675 lm	800 lm	80	3000 K	120 V
<b>6024LED-4K</b>	24"	8 W	675 lm	800 lm	80	4000 K	120 V
<b>6036LED</b>	36"	12 W	1080 lm	1200 lm	80	3000 K	120 V
<b>6036LED-4K</b>	36"	12 W	1080 lm	1200 lm	80	4000 K	120 V
<b>6048LED</b>	48"	16 W	1300 lm	1800 lm	80	3000 K	120 V
<b>6048LED-4K</b>	48"	16 W	1300 lm	1800 lm	80	4000 K	120 V

### Specifications

Uniform light output  
 Over 50,000 hours of service life  
 Dimmable with regular low-voltage electronic dimmers  
 Smooth linear wide spread  
 Minimal heat emission  
 No UV light emission  
 Very low profile  
 Robust construction  
 Multiple fixtures can be linked together (up to 200W)

### \*Note:

Junction box model 6000-JB or power cord model 6000-ACCPC are required for installation. Sold separately.

### Finish

**SBA** Sandblasted aluminum

### Accessories

**6000-ACCE06**

6" extension cord

**6000-ACCE24**

24" extension cord

**6000-ACCE60**

60" extension cord

**6000-ACCLR**

Kit of left and right L connectors

**6000-ACCPC**

6' power cord

**6000-JB**


Junction box

### Order example

**6009LED-SBA**

9" LED cove strip with a 3W LED array with 250 lumens at 3000K in a sandblasted aluminum finish

### 60\_LED



**6009** 9"

**6012** 12"

**6024** 24"

**6036** 36"

**6048** 48"

