


## Smooth baffle, square

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>RGR2SQ-CC</b>	2"	8 W	600 lm	750 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>RGR4SQ-CC</b>	4"	14 W	990 lm	1200 lm	90		120 V
<b>RGR6SQ-CC</b>	6"	20 W	1600 lm	1900 lm	90		120 V

### Specifications

Every fixture includes a junction box with integrated dimmable driver  
 Can be daisy chained  
 Superior LED performance and lifespan  
 Regressed light source  
 Minimal heat emission  
 Aluminum construction  
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 40° beam angle  
 Suitable for wet locations  
 JA8 Certified  
 Refer to website for dimmer compatibility  
 Ideal operating temperature: -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

### Accessories

- RFP-UNI**  
Universal rough-in plate
- RFP-23**  
Rough-in plate for 2" and 3" models
- RFP-46**  
Rough-in plate for 4" and 6" models

### Order example

**RGR2SQ-CC-SN**  
 Dimmable RGR2SQ-CC 2" square regressed LED fixture in a satin nickel finish

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

