

LED gimbal

There are moments when you want the ability to direct light as you please. With our LED Gimbal recessed fixture, this has now become a reality with the easiest of installations.



WET



SWIVEL/DIRECTIONAL



ENERGY STAR




Intertek



IC RATED



JA8 CERTIFIED



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
LEDDOWNG3-CC	3"	8 W	600 lm	635 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
LEDDOWNG4-CC	4"	8 W	600 lm	635 lm			
GMB4-CC	4"	11 W	810 lm	1000 lm			

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained
 Superior LED performance and lifespan
 30° tilting, 360° rotation
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K
 Low profile
 40° beam spread
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 JA8 Certified
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature: -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **SN** Satin Nickel
- **WH** White

Accessories


- RFP-UNI**
Universal rough-in plate
- RFP-23**
Rough-in plate for 2" and 3" models
- RFP-46**
Rough-in plate for 4" and 6" models



Order example


LEDDOWNG3-CC-BK
 3" gimbal recessed downlight with 600 Lumens at 3000 K in a black finish



Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

LEDDOWNG3-CC Ø2 3/4" 



LEDDOWNG4-CC Ø2 3/4" 



GMB4-CC Ø4 1/4" 

