


# High-powered commercial downlight

Dals' new high-powered recessed downlight is a go-to for your commercial projects. With its five color temperatures to choose from, a cast aluminum housing, high lumen output, and indoor/outdoor rating, this can be installed just about anywhere. From clinics to schools and hotels to boutiques, this is the only slim recessed fixture you will need.



RECESSED



**NEW**

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>HPD4-CC</b>	4"	20 W	1415 lm	1555 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>HPD6-CC</b>	6"	30 W	2100 lm	2310 lm			
<b>HPD8-CC</b>	8"	40 W	2600 lm	2850 lm			

**Specifications**

Every fixture includes a junction box with an integrated driver  
 Over 35,000 hours service life  
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K  
 Smooth 360° wide spread  
 90° beam angle  
 Cast aluminum construction  
 Suitable for wet locations  
 Compatible with TRIAC, ELV and 0-10 V dimmers  
 Refer to website for dimmer compatibility  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 5-year warranty

**Finish**

○ **WH** White

**Options**

**HPD4-CC-V-WH**  
 4" high-powered downlight with input for 0/10V, 120-277-347V

**HPD6-CC-V-WH**  
 6" high-powered downlight with input for 0/10V, 120-277-347V

**HPD8-CC-V-WH**  
 8" high-powered downlight with input for 0/10V, 120-277-347V

**Accessories**

**RFP-46 (HPD4, HPD6)**  
 Rough-in plate

**RFP-58 (HPD8)**  
 Rough-in plate


**Order example**

**HPD6-CC**  
 Dimmable 6" high-powered commercial downlight in a white finish


**Note**

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

**HPD4-CC**      Ø4 1/4" 



**HPD6-CC**      Ø6 1/2" 



**HPD8-CC**      Ø7 1/2" 

