SwivLED strip

To swivel or not to swivel is the question. With an ultra-slim profile, our LED strips can be fixed or flexible. Because you have both types of brackets included with each model, the choice is yours.

DRY

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
SWIVLED12	13.125"	3.2 W	270 lm	300 lm	80	3000 K	12 V
SWIVLED12-4K	13.125"	3.1 W	275 lm	300 lm	80	4000 K	12 V
SWIVLEDHP	13.125"	4.5 W	420 lm	600 lm	80	3000 K	12 V
SWIVLEDHP-4K	13.125"	4.5 W	440 lm	600 lm	80	4000 K	12 V

Specifications

Over 50,000 hours of service life
10" (25 cm) power cord included
Smooth linear wide spread
Minimal heat emission
No UV light emission
Multiple fixtures can be linked together
(Up to 4x SWIVLED in series
Up to 8x SWIVLEDHP in series)
Refer to website for dimmer compatibility
5-year warranty

Note

Plug-in or hard-wired power supply required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALS representative for more information.

Power supplies: plug-in

ETR-LED10WPI
12VDC/10W class 2 LED driver

ETR-LED24WPI
12VDC/24W class 2 LED driver

Power supplies: hard-wired

BT06DIM-IC
6W dimmable LED hardwire driver

BT12DIM-IC
12W dimmable LED hardwire driver

BT24DIM-IC
24W dimmable LED hardwire driver

BT36DIM
36W dimmable LED hardwire driver

BT48DIM
48W dimmable LED hardwire driver

Accessories

SWIVLEDEXT-10
10" extension cord

SWIVLEDEXT-36
36" extension cord

SWIVLEDEXT-60
60" interconnection harness

SWIVLEDACC-45VCLIP
45° clips

SWIVLED-CC10-OUTPUT
10" output connector

Finish

● **SBA** Sandblasted aluminum

Order example

SWIVLEDHP-SBA
SwivLED high-power strip with a 4.5W LED array, with 420 lumens at 3000K in a sandblasted aluminum finish

---

SWIVLED_

*Add 12.5" for each additional unit

13.125"

0.4"
0.625"