

# Etch

The Etch range of circular recessed downlights, characterised by a deep-set LED position, provides a functional solution to general lighting without the uncomfortable glare.

**NEW**

WET LOW-GLARE

Intertek IC RATED

AIR TIGHT

COLOR TEMPERATURE

2700k 3000k 3500k 4000k 5000k



| Model   | Size | Watts | Delivered lumens | CRI | Color °T          | Voltage |
|---------|------|-------|------------------|-----|-------------------|---------|
| DDP4-CC | 4"   | 15 W  | 1000 lm          | 90  | 2700, 3000, 3500, | 120 V   |
| DDP6-CC | 6"   | 20 W  | 1500 lm          |     | 4000, 5000 K      |         |

### Specifications

Every fixture includes a junction box with an integrated driver

Over 50,000 hours of service life

Can be daisy chained

Smooth 360° wide spread

Minimal heat emission

Frosted lens

Edge lit technology

Cast aluminum construction

Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K

Easy-access CCT switch on panel wire

Very low profile

IC certification (suitable for direct contact with insulation)

Air-tight certified as per ASTM E283-04

Suitable for wet locations

Ideal operating temperature: -20° to 40° C

Refer to website for dimmer compatibility

5-year warranty

### Finish

○ WH White

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

### Order example

#### DDP4-CC-WH

White 4" deep regressed panel with 1000 lumens at 3000 K

### Accessories

#### RFP-46

Rough-in plate

#### RFP-UNI

Universal rough-in plate

#### DDP4-TRIM-BK


4" recessed panel trim in black


#### DDP6-TRIM-BK

6" recessed panel trim in black



DDP4-CC

Ø4-1/4" 



DDP6-CC

Ø6-1/2" 

