

Revolve

Our Recessed family has grown with a new range of adjustable downlights. The effortless design and high functionality of these fixtures are sure to make a welcome addition in any room.

- UPGRADE**
- WET**
- LOW-GLARE**
- ENERGY STAR**
- ETL US Intertek**
- IC RATED**
- JA8 CERTIFIED**
- WARM DIMMING***
- 30° SWIVEL/DIRECTIONAL**
- AIR TIGHT**
- COLOR TEMPERATURE**
2700k 3000k 3500k 4000k 5000k



*Models GBR35-DW , GBR04-DW, GBR06-DW only

Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
GBR35-CC	3.5"	12 W	860 lm	90	2700, 3000, 3500, 4000, 5000 K	120V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
GBR04-CC	4"	15 W	1240 lm				
GBR06-CC	6"	20 W	1500 lm				
GBR35-DW	3.5"	12 W	860 lm	90	3000 K - 2200 K		
GBR04-DW	4"	15 W	1240 lm				
GBR06-DW	6"	20 W	1500 lm				

Specifications

Every fixture includes a junction box with an integrated driver
 Over 50,000 hours service life
 Switch-selectable CCT: 2700 K/ 3000 K/3500 K/4000 K/5000 K (GBRXX-CC models only)
 Dim-to-warm technology, dims from 3000 K to 2200 K to mimic incandescent light (GBRXX-DW models only)
 40° beam angle
 30° tilting, 360° rotation
 Cast aluminum construction
 Suitable for wet locations
 Refer to website for dimmer compatibility
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 5-year warranty

Finish

- **BK** Black (GBRXX-CC models only)
- **WH** White

Accessories

- RFP-35 (GBR35)**
Rough-in plate
- RFP-UNI (GBR04, GBR06)**
Universal rough-in plate
- RFP-46 (GBR04, GBR06)**
Rough-in plate
- REC-CC-EXT8FT (GBRXX-CC)**
8-foot extension cable
- REC-CC-EXT20FT (GBRXX-CC)**
20-foot extension cable
- REC-3K-EXT8FT (GBRXX-DW)**
8-foot extension cable
- REC-3K-EXT20FT (GBRXX-DW)**
20-foot extension cable

Multi-voltage ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

