

GLAZED PORCELAIN MOSAICS

# RETRO ROUNNDS™



 **daltile**<sup>®</sup>  
DESIGN WITH CONFIDENCE™

# RETRO ROUNDS™

GLAZED PORCELAIN MOSAICS



## A MODERN TAKE ON YOUR FAVORITE RETRO LOOK

Nostalgic with a contemporary twist, Retro Rounds brighten up walls, backsplashes and even pool linings. From Cherry Red and Orange Soda to Cobalt Circle and Daffodil Yellow, 13 vibrant color options make up this delightful collection including a classic polka dot option. Complementary matte finishes extend this retro look to the floor.

- **GREAT FOR CONTEMPORARY OR TRADITIONAL SPACES**
  - Mix of classic and contemporary colors
  - Timeless penny round shape
- **MULTITUDE OF OPTIONS**
  - Available in gloss and matte finishes for use on the floor and wall
  - Beautiful color varieties to match any space

Above and cover photos feature Saddle Brown.

# RETRO ROUNDS™

GLAZED PORCELAIN MOSAICS


GLAZED PORCELAIN MOSAICS




BOLD WHITE GLOSS RR01




BOLD WHITE MATTE RR02




POLKA DOT GLOSS RR03




POLKA DOT MATTE RR04




SMOKY GRAY RR12



ENGINE GRAY RR13




CANVAS BLACK GLOSS RR14




CANVAS BLACK MATTE RR15




CREAM SODA RR05




SADDLE BROWN RR06




DENIM BLUE RR10




COBALT CIRCLE RR11



DAFFODIL YELLOW RR07



ORANGE SODA RR08



CHERRY RED RR09

# RETRO ROUNDS™

## GLAZED PORCELAIN MOSAICS



### SIZES

		SQ.FT. CARTON	PCS. PER CARTON
Penny Round Porcelain Mosaic Decorative Accent (Mesh-Mounted)	12-7/16" x 11-9/16" Sheet (31.60 cm x 29.40 cm Sheet)	10	10
	RR03 & RR04 only 13-1/4" x 11-9/16" Sheet (33.60 cm x 29.40 cm Sheet)	10.63	10

### INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
3/16"	Approximately 1/8"

### TEST RESULTS (Matte Finish)

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant
Dynamoc C.O.F.	A137.1	Wet: < 0.42
Abrasion Resistance (PEI)	ISO 10545-7	3

A DCOF value of  $\geq 0.42$  is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of  $\geq 0.60$  referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™ please visit <http://daltile.com/information/DCOF>.

### TEST RESULTS (Gloss Finish)

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant



EXTERIOR PRODUCT



By their very design, DalTile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).

### RESIDENTIAL USAGE

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W			

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.

### COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios*	✓	✓			
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops					
Pool Decking					
Pool Linings	✓	✓	✓	✓	✓

\*Matte colors only suitable for residential and light commercial floors not subject to outside foot traffic.

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.

### SHADE VARIATION

SOLIDS		LOW (V1) Consistent color within each tile, and from tile to tile
PATTERNS		RANDOM (V4) Considerable variation from tile to tile

### NOTES

**Manufacturer Warning:** Polished tiles have a dynamic coefficient of friction less than 0.42 as measured by the DCOF Acutest method. Tiles with DCOF Acutest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall or personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Since there is shade variation in all products, the tile supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at [daltile.com/Factors](http://daltile.com/Factors).

