

Flanged Contemporary Bath Accessories

Installation, Use & Care Instructions



Thank you for your purchase, please enjoy your new Contemporary Corner Shelf. These products are designed for easy installation. They complement any ceramic, porcelain, metal or stone tile.

MATERIAL INSPECTION

The owner or owner's representative is responsible for determining the acceptability of the product prior to installation. Each box should be opened and inspected upon delivery of the order.

No adjustments will be made after installation.

Q-SEAL™ PERMANENT PROTECTION

This product is protected by Q-Seal, a permanent sealer that is water and stain resistant, protects against abrasion. Q-Seal features Ultra-Fresh® anti-microbial protection, which inhibits the growth of stain and odor-causing mold and mildew. Q-Seal is factory-applied and never needs re-sealing. Stone or grout sealer inadvertently applied to the surface cannot penetrate or adversely affect Q-Seal. Simply wipe excess sealer off of the shelf.



APPLICATIONS & USES

	Suitable
Walls / Backsplashes	√
Countertops	
Pool Linings	

Interior Use Only; Not suitable for painted surfaces. Corner shelves may be installed in wet areas such as backsplashes, bathroom walls, shower enclosures and steam rooms, but are not recommended in swimming pools or hot tubs because pool chemicals may harm the protective coating.

SETTING MATERIALS

Select one of the following two adhesives.

- THIN-SET: A liquid latex (polymer) fortified premium thin-set Portland cement mortar conforming to ANSI A118.4.
- EPOXY ADHESIVES: A water-cleanable epoxy mortar conforming to ANSI A118.3.

INSTALLATIONS INSTRUCTIONS

STEP 1 – POSITION

Set wall tile to height accessory will be located.

STEP 2 – APPLY RECOMMENDED ADHESIVE

Following the adhesive manufacturer's instructions, trowel a layer of adhesive on the dove-tails (teeth) of each accessory prior to placing on the combed adhesive bed to obtain 100% coverage.

STEP 3 – HOLD AND SUPPORT IN PLACE

Dove-tail should be pushed into adhesive to ensure good contact. The accessory's back should overlap the wall tile. Continue wall installation around the accessory, noting that the accessory's back should overlap the wall tile. Tape accessory in place until adhesive bonds.

STEP 4 - CAULK

Once fully cured, thoroughly caulk around the perimeter of the shelf to seal out water.

STEP 5 - CLEANING

To clean your corner shelf, please use a damp sponge together with warm, soapy water or an ordinary household cleaner. Do NOT use ACID based products, liquid abrasive cleaners or harsh detergents/chemicals.

CARE AND MAINTENANCE

- To clean, use an ordinary household cleaner. For best results, we recommend a liquid, non-abrasive cleaner.
- Liquid abrasive household cleaners should only be used after being tested in a small, inconspicuous area to ensure that no damage will result.
- Do NOT clean with scouring pads, steel wool or other abrasive implements or damage to the surface may result.
- Cleaners containing ammonia, bleach or other harsh chemicals should be wiped up shortly after application or damage to the surface may result.

LIMITED WARRANTY

Dal-Tile provides a limited warranty on its products. The term of this warranty may be found at: www.daltile.com/information/warranty