



FLOOR | WALL

FLORENTINE™

GLAZED PORCELAIN FLOOR & MOSAIC, GLAZED CERAMIC WALL
with REVEAL IMAGING®

 **daltile**®
IMAGINE WHAT'S POSSIBLE™



Cover photo features Nociolla 12 x 24 floor tile in staggered brick-joint pattern on the floor and Nociolla 12 x 24 wall tile in grid pattern on the wall. Above photo features Nociolla 12 x 24 floor tile on the floor, with an inset of Argento 12 x 24, Stone À la Mod™ Urban Bluestone mosaic border, and Imperial Stone Medallion in the center. Wall features Nociolla 12 x 24 in a brick-joint pattern.

Revel in the Exquisite Look of Marble & Stone

Florentine™ from Daltile is for those who admire the elegance of marble and stone, but desire the durability and low maintenance of ceramic tile. This timeless style mimics the unique tones of marble and stone with a color palette of crisp whites, neutral tans and fresh grays. Transform your area with the Florentine collection.

- VARIETY OF NATURAL STONE VISUALS
 - Each color emulates a unique and striking replication of natural marble and stone with Reveal Imaging®
- GLOSSY & MATTE TILES
 - High gloss wall tile and coordinating matte floor and mosaics create dynamic visual appeal
- LOW MAINTENANCE & DURABILITY
 - Perfect for areas requiring low maintenance and durability in high-traffic areas without sacrificing style
- ATTRACTIVE PRICE POINT
 - Cost-efficient alternative when compared to natural stone



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING®



TRU-EDGE™

All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.

CERTIFIED PORCELAIN
TILE
0.5% or less water absorption

GLAZED PORCELAIN FLOOR TILE



CARRARA FL06



MARFIL FL07



ARGENTO FL08



NOCIOLLA FL09

GLAZED PORCELAIN 2 x 4 MOSAIC



CARRARA FL06



MARFIL FL07



ARGENTO FL08



NOCIOLLA FL09

GLAZED CERAMIC WALL TILE



CARRARA FL06



MARFIL FL07



ARGENTO FL08



NOCIOLLA FL09

FLORENTINE™

GLAZED PORCELAIN FLOOR & MOSAIC, GLAZED CERAMIC WALL with REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 24 Floor Tile (Matte)	(23-7/16" x 23-7/16") (59.44 cm x 59.44 cm)	3/8"	15.20	4
	12 x 24 Floor Tile (Matte)	(11-5/8" x 23-7/16") (29.56 cm x 59.44 cm)	3/8"	15.12	8
	12 x 12 Floor Tile (Matte)	(11-1/2" x 11-1/2") (29.56 cm x 29.56 cm)	3/8"	12.22	13
	12 x 24 Wall Tile (Glossy)	(11-5/8" x 23-7/16") (29.56 cm x 59.44 cm)	3/8"	11.64	6
	10 x 14 Wall Tile (Glossy)	(9-27/32" x 13-3/4") (25.00 cm x 35.00 cm)	3/8"	11.62	12
	2 x 4 Brick-joint Mosaic (Matte) (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	3/8"	10.00	12

FLOOR APPLICATIONS

(Excludes Wall Tile)	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓**
Pool Linings	✓***

APPLICATION NOTES:

* Floor tile and mosaic suitable. Mosaic also suitable for residential and light commercial shower floors.

** Floor tile and mosaic only

*** Mosaic only

Floor tile suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

Wall tile and mosaic suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

TRIM

	Type	Number	Size	Pieces per Carton
	Floor Bullnose (Matte) ■	P-43C9F	3 x 12	30
	Wall Bullnose (Glossy)	S-43C9WX (12" side)	3 x 12	30
	Wall Bullnose (Glossy)	S-4310 (10" side)	3 x 10	30
	Wall Bullnose Corner (Glossy)	SN-4310	3 x 3	30

■ Floor bullnose trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
10 x 14 Wall : 1/16" 12 x 24 Wall, Floor and Mosaic : 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%)	High (V3)

TEST RESULTS

	ASTM#	Floor & Mosaic Result Matte Finish	Wall Result Glossy Finish
Water Absorption	C373	< 0.5%	< 20.0%
Breaking Strength	C648	> 275 lbs	120-230 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	3-4	N/A

For additional information, visit daltile.com/information/TestResults.

NOTES

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at:
GET.DALTILE.COM



7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (1/17)